# **APPENDICES**



# REPORT OF THE GEOTECHNICAL INVESTIGATION

SUBURBAN PIPELINE PROJECT - PHASE II
WATER DISTRIBUTION SYSTEM
MANATEE COUNTY, FLORIDA



December 16, 2009

Manatee County Government 1022 - 26<sup>th</sup> Avenue East Bradenton, Florida 34208

Attention:

Mr. Chuck Froman

Project Manager

RE: Report of the Geotechnical Investigation
Suburban Pipeline Project - Phase II
Water Distribution System
Manatee County, Florida
Our File: DES 096393
Work Assignment #9
IFAS # WO900254

Dear Chuck:

Pursuant to prior authorization and the above referenced Work Assignment #9, **DRIGGERS ENGINEERING SERVICES, INC.** has completed the geotechnical investigation for Phase II of the subject project. Presented herein are the results of our field and laboratory studies together with a general discussion of subsurface soil and groundwater conditions along the proposed pipeline alignments. Results of our geotechnical studies for Phase I of the project were submitted in our report dated July 8, 2009.

#### **GEOTECHNICAL INVESTIGATION PROGRAM**

A program of shallow depth exploratory borings and laboratory classification testing was undertaken to characterize the general nature of the subsurface soils and potential impacts with respect to the planned potable water distribution system.

**FIELD INVESTIGATION** - Plates I-A through I-DD of the report attachments identify the respective positioning of forty-two (42) shallow classification borings which were generally spaced at the requested nominal 500 feet apart to investigate soil and groundwater conditions. The classification borings were typically advanced to the requested depth of 8 feet below existing grade. The locations of the classification borings were selected in the field by our personnel utilizing the 60% Design Submittal pipeline alignment plans, dated September, 2009, recently provided by CH<sub>2</sub>M Hill, and the marked locations of existing buried utility lines. The boring locations depicted are considered approximate since they were not surveyed. While some ground surface spot elevations are shown on the plans provided to us, ground surface elevations at the boring locations were not provided and no estimates were made from the available data.

The classification borings were conducted utilizing hand auger equipment wherein the soils were classified virtually continuously below existing grades to the termination depth. Logs of the classification borings are presented in the report attachments reflecting visual together with estimated Unified Soil Classification. Groundwater depths measured during the course of our field investigation are noted on each respective boring log.

LABORATORY CLASSIFICATION TESTS - A limited laboratory classification testing program was undertaken to aid in characterizing the engineering properties of the subsurface soils. Our laboratory tests included grainsize analyses, Atterberg liquid and plastic limits and organic content tests. Selected samples were also tested for corrosivity potential. Results are presented on the Summary of Laboratory Test Results in the appendix. Results of the grainsize analyses are included in the report attachments reflecting the percent finer (by weight) versus the equivalent grain diameter or U.S. Standard Sieve size.

## GENERALIZED SUBSURFACE CONDITIONS

The results of our classification borings indicate that the subsurface soils typically consist of fine sands comprising the SP to SP-SM Unified Soil Classifications. Also penetrated were occasional zones of silty to clayey sands (SM to SC soils) interbedded with the relatively cleaner sands. Based upon our laboratory testing program, the fine sands typically contain minimal silt and clay fines, less than 10% by weight. However, some of the silty to clayey sand seams exhibited fines contents of up to nearly 40 percent, with the clayey sands exhibiting low to moderate plasticity characteristics. Some of the sands also contained traces to various concentrations of shell and occasional rock fragments.

Note also that thin seams of organic sands and peat (muck) were encountered within a depth range of about 1.5 to 5.5 feet at boring locations HA-2-7 and HA-2-9. Results of organic content testing suggest that these soils have organic contents in the range of 9.7 to 11.9 percent, by weight. Other zones of organic stained sands with organic contents less than 5 percent were also penetrated at boring locations HA-2-10, HA-2-11, HA-2-27, HA-2-32 through HA-2-38 and HA-2-40.

An exception to the general trend occurred at boring location HA-2-3 where refusal to hand auger penetration was encountered at a depth of 4.0 feet. Note that at several boring locations in Phase I of the project, a discontinuous, thin rock unit was first encountered at varying depths ranging from about 0.8 to 5 feet beneath present grades. Review of the Manatee County Soil Survey indicates some areas of Broward and Wabasso Variant soils within the project limits. The typical profile of these soil types indicates that shallow depth limestone, limestone boulders or gravel may exist.

Groundwater was typically measured within a depth range of 3.3 to 7.9 feet below existing grade at the time of our geotechnical studies. At several locations, groundwater was not evident within the boring completion depth of 8 feet beneath present grade. It should be noted that these classification borings were conducted from the middle of November to early December, following the typical wet season. There is certainly the potential for groundwater to occur at shallower depths in response to more frequent or prolonged rainfall. Water may also occur in a temporarily perched state above the low permeability silty to clayey sand zones.

The Soil Survey indicates the presence of EauGallie-Myakka, Felda, Chobee, Okeelanta and Canova soils, in addition to the aforementioned Broward and Wabasso Variant soils, in the project area. Under natural conditions, seasonal high groundwater levels for EauGallie-Myakka soils would be between 0.5 and 1.5 feet below grade. Seasonal high groundwater for Felda, Chobee and Okeelanta soils may occur within a foot of the ground surface. Depressional soils such as Canova soils may, under natural conditions, have water levels above the ground surface. It should be noted that the Soil Survey estimates do not consider the effects of development and drainage improvements, all of which can affect groundwater levels. It appears that any depressional areas were filled during development of the area. In consideration of the time of year, the antecedent rainfall and the Soil Survey information, we would anticipate no more than a nominal 1.5 foot rise in groundwater above current water levels during the normal wet season. Confirmation of potential seasonal fluctuations would necessitate installing shallow piezometers and monitoring groundwater levels during the wet season.

#### GEOTECHNICAL EVALUATION AND RECOMMENDATIONS

PLANNED CONSTRUCTION - The project area is west of U. S. 41 and is bounded roughly by 26<sup>th</sup> Street West on the west, 53<sup>rd</sup> Avenue West on the north and 58<sup>th</sup> Avenue Drive on the South. We understand that the project will include the construction of 6-inch and 8-inch diameter HDPE potable water mains. Based upon plans provided and discussions with Mr. Bob Cannarella, P.E. with CH<sub>2</sub>M Hill, the water mains will generally be constructed utilizing either directional drilling or standard cut and cover construction, with a minimum of 3 feet of cover and a burial depth of no more than about 5 feet in order to facilitate service and other connections. The main pipelines will generally be located outside of existing pavements, with services crossing beneath the existing streets.

**PIPELINE SUBGRADE CONDITIONS** - Our geotechnical studies suggest that the subgrade soils within the depth of exploration typically consist of fine sands containing some to minimal silt fines. These soil types should generally be suitable for pipe support provided that the subgrade is prepared in accordance with project specifications. In general, this will necessitate appropriate compaction at the bottom of excavation and throughout backfill soils required to re-establish existing grades in accordance with Manatee County specifications.

**SUITABILITY OF EXCAVATED SOILS FOR USE AS BACKFILL** - Fine sands indicated in our geotechnical studies will represent suitable materials for replacement and compaction as backfill following pipeline installation. These fine sands comprising the SP to SP-SM Unified Soil Classification should respond effectively to conventional vibratory compaction. Results of corrosivity testing suggest that the soils along the pipeline routes fall within the "Moderately Aggressive" FDOT corrosivity classification.

Where silty to clayey sands were evidenced, these soils typically occurred in relatively thin layers. Accordingly, the soils with increased fines and some plasticity can probably be mixed with the cleaner sands during the excavation and backfilling process to improve the workability of these soils. Similarly, the thin organic zones evidenced in several of the borings can probably be mixed with the overlying and underlying sands and incorporated in the backfill. Where highly organic soils or plastic soils may exist near the bottom of the excavation or in greater thickness than suggested by the program of borings, it may be necessary to undercut the highly organic or plastic soils at least 2 feet and replace these materials with properly compacted granular backfill or gravel so as to produce a firm and unyielding subgrade for subsequent pipeline construction and backfilling operations.

While refusal to hand auger penetration was encountered at only a single location, the exploratory borings conducted for Phase I of the project and the Soil Survey information indicate that shallow depth limestone, limestone boulders and limestone gravel could be present in some areas. Gravel sized material may be incorporated within the sandy backfill soils. Rocks larger than about 3 inches should be excluded. Of course, rocks and oversize materials should be excluded from the pipe zone to minimize the potential for damage to the pipe.

It is important to recognize that the soils may exist in a very low natural moisture content depending upon the rainfall occurring at the time of construction or at high moisture contents when excavated below the water table. Accordingly, the soils may require some adjustment in moisture content to achieve efficient and effective compaction. In general, it is beneficial to adjust moisture contents to within  $\pm 2\%$  of the optimum moisture as established by the Standard Proctor moisture-density relationship as set forth in AASHTO T-99.

**CONSTRUCTION CONSIDERATIONS** - We understand that much of the pipeline may be installed utilizing directional drilling. Care must be exercised during the directional drilling process in order to appropriately stabilize the horizontal borehole with drilling slurry so as to avoid potential caving of overlying soils that could cause unacceptable settlements to overlying or adjacent utilities, structures and pavements. Conversely, one must avoid over-pressuring the drilling slurry that could result in unacceptable discharge of drilling slurry to the ground surface. Shallow depth rock zones, which the Soil Survey suggests may exist in some areas, could also affect directionally drilled pipeline construction.

Portions of the pipeline, and certainly connections, will be constructed utilizing open-cutting and backfilling following pipeline installation. Depending on the depth of the cut, it may be necessary to adjust the excavation slope ratios to no steeper than about 1.5 horizontal to 1.0 vertical in order to minimize sloughing or caving during the backfilling operations. Utilization of this slope ratio will necessitate proper dewatering, where necessary, and protection of the slope with respect to erosion and sloughing. Alternatively, trench-box construction would be considered in lieu of a sloped excavation. Naturally, the contractor must comply with applicable OSHA requirements with respect to trench safety.

In anticipation of cut depths typically 4 to 5 feet or less, we would not anticipate the need for a significant amount of construction dewatering throughout the project. Of course, abnormal rainfall could produce higher than expected groundwater levels and necessitate some local management of groundwater during pipeline construction. In that event, we would envision that the dewatering could be effectively

accomplished by the application of a nominal 12 inch gravel drainage blanket of durable, washed limerock, granite or crushed concrete having a grading of no coarser than an FDOT No. 89. The gravel drainage blanket could then be used in conjunction with interior sumping in order to control groundwater levels below the invert of the pipeline and allow appropriate placement and compaction of the subgrade and backfill.

CONSTRUCTION INSPECTION AND TESTING - The authorized geotechnical investigation consisted of a series of relatively widely spaced, hand advanced classification borings intended to identify generalized subsurface conditions that may be expected throughout the project limits. Clearly, the potential exists that localized variations or unexpected conditions may occur that would warrant modifications in construction procedures. Accordingly, it will be important to implement an appropriate program of geotechnical inspection of any open cuts during the construction stage to assist in identifying any such anomalous conditions and to provide economical recommendations for any necessary remediation. Inspection should be performed by a qualified geotechnical inspector familiar with the detailed contents of this report.

Additionally, additional more closely spaced borings are suggested particularly in the vicinity of boring HA-2-3 where refusal to hand auger penetration was encountered, to aid in identifying the limits of the shallow depth rock zone. As noted, the Soil Survey suggests that this rock zone cold be more widespread than suggested by the authorized soil boring program.

Compaction testing will also be required during the subgrade preparation and backfilling operations to check that the soils are being compacted in accordance with Manatee County compaction requirements. The compaction tests should be conducted in such a manner so as to check that all of the backfill soils are being uniformly densified to project specification requirements.

**LIMITATIONS** - The geotechnical investigation program was undertaken to provide general information to assist in the design and construction of the planned facilities. Our investigation may not have included all information that the prospective contractor may require in the preparation of his bid proposal. The contractor is certainly encouraged to conduct such additional studies as he may deem necessary to qualify his proposal.

Our geotechnical investigation was limited to an examination of subsurface soil and groundwater conditions so as to address geotechnical design and construction issues. Studies relative to environmental issues or impacts was not within the authorized scope of services.

12-23-10

**DRIGGERS ENGINEERING SERVICES, INC.** appreciates the opportunity to serve you during this phase of the design stage of the water distribution system. Should you have any questions concerning our report, please do not hesitate to contact the undersigned at your convenience.

Respectfully submitted,

DRIGGERS ENGINEERING SERVICES, INC.

Nicholas T. Korecki, P.E.

Senior Geotechnical Engineer

reholast. Kerlelei

FL Registration No. 45529

Jame Driggers, P.E.

President

FL Registration No. 16989

NTK

NTK-REP\096393-II

Copies submitted:

- (3) Manatee County Government.; Attn: Chuck Froman
- (2) CH<sub>2</sub>M Hill.; Attn: Mr. Bob Cannarella, P.E.


### **APPENDIX**

PLATES I-A THROUGH 1-DD - TEST BORING LOCATION PLANS

HAND AUGER BORING LOGS

**SUMMARY OF LABORATORY TEST RESULTS** 

**GRAINSIZE ANALYSES** 



HAND AUGER BORING LOGS Driggers Engineering Services Incorporated



HAND AUGER BORING LOG									
PROJEC	T: Suburban Pipeline Project - Phase II	CLIENT:  Manatee County							
	Manatee County, Florida Project No.: DES 096393	WATER	DATE: 11/30/09						
TECHNIC	CIAN: M.B.	DATE: COMPLETION D 11/30/09 8.							
LOCATIO		TEST NUMBER: HA2-1							
	See Plate 1-00		7		72-1				
ELEV. (FT)	DESCRIPTION	DEPTH (FT)	SYMBOL		REMARI	KS			
	Brown Fine SAND with trace of shell and limestone fragments (SP)	0	.♥.:o						
	Brown and light brown Fine SAND with trace of shell fragments (SP)  Tan and light gray Fine SAND		▽						
	with trace of roots (SP)	2 -							
	Gray slightly silty Fine SAND with shell fragments (SP-SM)	4 -							
	Very light gray Fine SAND with trace of shell fragments (SP)		♥						
	Dark grayish-brown slightly silty Fine SAND (SP-SM)	6 -							
	Dark grayish-brown clayey Fine SAND (SC)		777						
	Brown Fine SAND (SP)	8 -							
			The state of the s						
			ma decembrantes de la constantes de la constante del constante de la constante del constante de la c						
		10 -	es e qui de la companya de la compan						
			over may proceed the state of t						
		12 -							
			energy property and the second party and the second						
		14 -				_			



	HAND AUGH	ER BORI	NG LO	G						
PROJECT: Suburban Pipeline Project - Phase II		CLIENT:  Manatee County								
	Manatee County, Florida	WATE	DATE:							
TECHNIC		DATE:		See "Note"	COMPLET	11/17/09 TON DEPTH:				
LOCATIO		11/17/09 8.0' TEST NUMBER:								
	See Plate I-A		HA2-2							
ELEV. (FT)	DESCRIPTION	DEPTH (FT)	SYMBOL		KS					
	Grayish-brown Fine SAND with some roots (SP)	0				***************************************				
	Gray Fine SAND with limestone fragments (SP) Brown Fine SAND (SP)	2	0.0							
	Brownish-gray slightly silty Fine SAND with shell and limestone fragments (SP-SM)	- 4								
	Brown Fine SAND (SP) Brownish-gray Fine SAND with some shell fragments and trace of dark brown Fine SAND (SP)	8 -			er Table n hin depth	ot encountered of 8.0'.				
		- 12 -								



PROJECT		ER BORING LOG   CLIENT:							
PROJECT	Suburban Pipeline Project - Phase II	Manatee County							
	Manatee County, Florida Project No.: DES 096393	WATER	R TABLE:	See "Note"		DATE: 11/17/09			
TECHNICI	AN:	DATE:			COMPLE	TION DEPTH:			
LOCATION	J.R	TEST N	11/1 IUMBER:	7/09	<u> </u>	4.0' *			
Т	See Plate I-X		1 . 1	<u> </u>	42-3	OLD-SALE-PORTER TO THE SALE PORTER TO THE SALE PORT			
ELEV. (FT)	DESCRIPTION	DEPTH (FT)	SYMBOL	REMARKS					
	Brownish-gray Fine SAND with some roots and shell fragments (SP)	0	7.7.		A. C				
	Dark gray Fine SAND (SP)								
	Brown Fine SAND (SP)	2							
	Light brown clayey Fine SAND with light orange veins (SC)								
	Light brownish-gray slightly silty, slightly clayey Fine SAND (SP-SM)	4 -	4:K!4; 4:K!4; 4:K!4;	* Encount	ered refu	sal at depth 4.0'.			
					_	at 4 Locations.			
					ter Table thin depth	not encountered n of 4.0'.			
		- 6 -							
			and described to the second						
		8							
		- 10 -							
		- 12 -							
		- 14 -							



HAND AUGER BORING LOG									
PROJEC	T: Suburban Pipeline Project - Phase II	CLIENT:  Manatee County							
the control of the co	Manatee County, Florida Project No.: DES 096393	WATER	WATER TABLE: DATE: 11/17						
TECHNIC	CIAN: M.M.	DATE: COMPLET				ION DEPTH: 8.0'			
LOCATIO	DN: See Plate I-B	TEST	IUMBER		\2-4				
	Occ i late i b					To a second seco			
ELEV. (FT)	DESCRIPTION	DEPTH (FT)	SYMBOL		REMARI	KS			
	Dark gray Fine SAND with roots (SP)	0							
	Dark gray Fine SAND with some pockets of weakly cemented, clayey Fine SAND (SP/SC)	2							
	Brown Fine SAND with seams of dark gray clayey Fine SAND (SP/SC)								
	Grayish-brown silty, slightly clayey Fine SAND(SM)	- 4							
		- 6							
	Tan and light brown Fine SAND (SP)								
	Light grayish-brown Fine SAND with shell fragments (SP)		7. '♥'. ♥'. ' ♥'. ♥'. ♥ 7. '♥'. ♥'						
		8							
			To the second se						
		10	The state of the s						
			and the second s						
		12	The second secon						
			- Annual Control of the Control of t						
		- 14 -							



	HAND AUG			3					
PROJECT:	Suburban Pipeline Project - Phase II	CLIENT:  Manatee County							
	Manatee County, Florida Project No.: DES 096393	WATE	WATER TABLE: DATE: 11/17/09						
TECHNICIA	#: M.M.	DATE:		17/09	COMPLETION DEPTH:	703			
LOCATION:	LOCATION:		NUMBER	:	8.0'				
	See Plate I-B				HA2-5	· · · · · · · · · · · · · · · · · · ·			
ELEV. (FT)	DESCRIPTION	DEPTH (FT)	SYMBOL		REMARKS				
	Dark gray Fine SAND with roots (SP)	0	7. (1. (1. (1. (1. (1. (1. (1. (1. (1. (1						
	Gray Fine SAND (SP)								
	Dark brown Fine SAND (SP)								
	Brown Fine SAND (SP)	2	-						
-		4							
	Dark brown Fine SAND (SP)	- 6							
	Light brown Fine SAND (SP)								
		8							
		10 -							
		12 -							
		14 -							



HAND AUGER BORING LOG										
Suburban Pipeline Project - Phase II Manatee County, Florida			CLIENT:  Manatee County  WATER TABLE:  DATE:							
TECHNIC	Project No.: DES 096393	DATE:		4.9'	COMPLET	11/17/09 ION DEPTH:				
LOCATIO	M.M.	[	11/ IUMBEF	/17/09		8.0'				
LOCATIC	See Plate I-C	1E31 N	IOMIDE	HA	2-6					
ELEV. (FT)	DESCRIPTION	DEPTH (FT)	SYMBOL		REMARI	KS				
	Brown Fine SAND with roots (SP)	0		200						
	Dark reddish-brown Fine SAND (SP)	- 2 -								
	Light brown Fine SAND (SP)									
	Brown Fine SAND (SP)	- 4 -		2						
	Light brown Fine SAND (SP)	- 6 -								
	Tan Fine SAND (SP)									
		- 8 -								
		- 10 -								
		40								
		- 12 -								
		- 14 -								



	HAND AUG	ER BORIN	G LO	3				
PROJECT	: Suburban Pipeline Project - Phase II Manatee County, Florida	CLIENT	: ! TABLE	:	e County	ATE:		
TECHNICI	Project No.: DES 096393	DATE:		5.7'	COMPLETIO	11/17/09 N DEPTH:		
	M.M.		DATE: COMPLETION DEPTH: 8.0' TEST NUMBER:					
LOCATION	V: See Plate I-C	TEST	UMBER	:: HA	12-7			
ELEV. (FT)	DESCRIPTION	DEPTH (FT)	SYMBOL					
	Dark grayish-brown Fine SAND with roots (SP)	0						
	Very dark brown organic, slightly silty Fine SAND (SP-SM/Pt)	- 2						
	Dark brown Fine SAND with some roots (SP)	- 4 -						
		- 6	75.75					
		8						
		- 10 -						
		- 12 -						
		14 -						



	HAND AUGE						
PROJECT	Γ: Suburban Pipeline Project - Phase II	CLIEN.	Γ:	Mar	natee County		
	Manatee County, Florida Project No.: DES 096393		R TABLE:	5.8'	<b>DATE</b> : 11/17/09		
TECHNIC	IÄN: M.M.	DATE:	11/1	7/09	COMPLETIO	<b>N DEPTH:</b> 8.0'	
LOCATIO	N: See Plate I-D	TEST	IUMBER:				
			占				
ELEV. (FT)	DESCRIPTION	DEPTH (FT)	SYMBOL		REMARKS		
	Brown Fine SAND with roots (SP)	0					
	Grayish-brown Fine SAND (SP)						
	Brown Fine SAND (SP)	2					
	Mottled gray and brown Fine SAND (SP)	- 4					
	Brown Fine SAND (SP)						
		6					
		8					
		- 10					
		- 12	and the second s				
		- 14 -	and the state of t				



	HAND AUGI	ER BORIN	G LOC	3		op de la companya de		
PROJEC	Suburban Pipeline Project - Phase II	CLIENT:  Manatee County  WATER TABLE:  DATE:						
entire de la constante de la c	Manatee County, Florida Project No.: DES 096393		IADLE	7.1'		11/17/09		
TECHNIC	CIAN: M.M.	DATE:	111	17/09	COMPLET	TION DEPTH: 8.0'		
LOCATIO	N:	TEST N	UMBER	•	<u> </u>	0.0		
	See Plate I-D		<del></del>	HA	\2-9			
ELEV. (FT)	DESCRIPTION	DEPTH (FT)	SYMBOL		REMARKS			
(FT)	Brown Fine SAND (SP)  Light gray Fine SAND (SP)  Very dark brown organic Fine SAND with trace of roots (SP-SM/Pt)  Dark reddish-brown Fine SAND (SP)  Very dark brown slightly organic Fine SAND (SP)	(FT) 0 2 - 4 - 6 - 10 - 12 -	SYN (COLUMN COLUMN COLU					
		- 14						



HAND AUGER BORING LOG									
PROJEC	T: Suburban Pipeline Project - Phase II	CLIENT:  Manatee County							
	Manatee County, Florida Project No.: DES 096393		R TABLE	7.7'		<b>DATE:</b> 11/17/09			
TECHNIC	CIAN: J.R.	DATE:	11/	17/09	COMPLET	ION DEPTH: 8.0'			
LOCATIO	ON: See Plate I-F	TEST N							
	See Flate I-I	T	7	11/2	A2-10				
ELEV. (FT)	DESCRIPTION	DEPTH (FT)	SYMBOL		REMAR	KS			
	Dark gray Fine SAND with some roots (SP)	0	なったがない。						
	Gray Fine SAND (SP)	2							
	Very dark brown slightly organic Fine SAND (SP)	4							
	Dark reddish-brown Fine SAND (SP)								
	Dark brown Fine SAND (SP)	6							
	Reddish-brown Fine SAND (SP)								
		8							
		- 10 -							
		- 12 -							
			angeneral de la company de la						
		- 14 -							



	HAND AUGE	R BORIN	IG LO	G		Microsoft and the High County
PROJECT	Suburban Pipeline Project - Phase II Manatee County, Florida	CLIEN WATER	Γ: R TABLE	Ma ≣: 5.3'	anatee County	DATE: 11/17/09
TECHNICI	Project No.: DES 096393  AN:  J.R.	DATE:	11	5.3 /17/09	COMPLET	FION DEPTH: 8.0'
LOCATIO	V: See Plate I-F	TEST	IUMBER	₹:	HA2-11	0.0
ELEV. (FT)	DESCRIPTION	DEPTH (FT)	SYMBOL		REMAR	KS
	Dark gray Fine SAND with some roots (SP)	0		25		
	Light brown Fine SAND (SP)	2				
	Tan Fine SAND (SP)					
	Dark brown slightly silty Fine SAND with finely divided organic material (SP-SM)	4				
	Brown Fine SAND (SP)	6	+ + +   - + + + + + + + + + + + + + +	ration and those to a large		
-	Light brown Fine SAND (SP)					
		8 -		The second secon		
		10 -				
		12 -				
		- 14 -				



HAND AUGER BORING LOG									
PROJEC	Suburban Pipeline Project - Phase II Manatee County, Florida	CLIEN	Γ: R TABLE	:	natee County	DATE:			
TECHNIC	Project No.: DES 096393	DATE:	·····	5.5'	COMPLET	11/17/09 NON DEPTH:			
LOCATIO	J.R.	TEST	11/ IUMBER	17/09 :		8.0'			
	See Plate I-E			T	HA2-12				
ELEV. (FT)	DESCRIPTION	DEPTH (FT)	SYMBOL		REMAR	KS			
	Mottled gray and brown Fine SAND with trace of roots (SP)	0	ン : ^ : : ^ :						
	Tan Fine SAND (SP)	- 2 -							
	Grayish-brown Fine SAND (SP)								
	Citation brown in the court of	- 4 -							
	Dark grayish-brown Fine SAND(SP)	- 6 -							
	Brown Fine SAND (SP)	- 8 -							
		- 10 -							
		12 -							
		14 -							



PROJECT: Suburban Pipeline Project - Phase II			CLIENT:  Manatee County						
	Suburban Pipeline Project - Phase II  Manatee County, Florida  Project No.: DES 096393	WATER	R TABLE:		DATE: 11/17/09				
ECHNICIAN	<b>4:</b>	DATE:			COMPLETION DEPTH:				
OCATION:	J.R.	TEST	11/17/09 IUMBER:	L	8.0'				
	See Plate I-G			HA2-	-13				
ELEV. (FT)	DESCRIPTION	DEPTH (FT)	SYMBOL		REMARKS				
	Brown Fine SAND with trace of roots (SP)	0	~ ;;						
	Light grayish-brown Fine SAND (SP)								
	•	2							
	Light brown slightly silty Fine SAND with light orange veins (SP-SM)								
	Light brown Fine SAND (SP)	4							
designation of the second		- 6							
		8							
		- 10 -							
		12 -							
		- 14 -							



	HAND AUG						
PROJECT:	Suburban Pipeline Project - Phase II Manatee County, Florida	CLIENT:  Manatee County  WATER TABLE:  DATE:					
	Project No.: DES 096393			6.6'	11/17/09		
ECHNICIAN:	: M.M.	DATE:	11/17	/09	COMPLETION DEPTH: 8.0'		
OCATION:		TEST N	IUMBER:				
	See Plate I-H				HA2-14		
ELEV. (FT)	DESCRIPTION	DEPTH (FT)	SYMBOL		REMARKS		
	Light brown Fine SAND	0					
	with trace of roots (SP)						
-	Tan Fine SAND						
	with limestone fragments (SP)		0 0				
	with innectorio riagmonico (or )		5 0				
		2	0:0:				
	Tan Fine SAND (SP)						
	Light brown slightly silty Fine SAND (SP-SM)						
	Light grayish-brown Fine SAND (SP)	- 4					
	Tan Fine SAND (SP)						
		- 6					
			ļ:::::::				
		8 -					
		0					
			1				
		1.5					
		10	1				
- Andrews - Andr			1				
-							
			1				
			1 1				
		- 12 -	1				
			1 1				
		- 14 -					
		14					



PROJECT	CLIENT:						
	Suburban Pipeline Project - Phase II Manatee County, Florida Project No.: DES 096393	1	R TABLE:	Ma : 7.8'	natee County	DATE: 11/17/09	
TECHNIC	IAN: M.M.	DATE:	11/1	17/09	COMPLE	TION DEPTH: 8.0'	
LOCATIO	N: See Plate I-J	TEST N	IUMBER	:	HA2-15		
			7				
ELEV. (FT)	DESCRIPTION	DEPTH (FT)	SYMBOL		REMA	RKS	
	Dark grayish-brown Fine SAND with roots (SP)	0				, , , , , , , , , , , , , , , , , , ,	
	Light brown Fine SAND (SP)	2					
-		4					
	Tan Fine SAND (SP)	- 6					
	Light grayish-brown slightly silty Fine SAND with shell fragments (SP-SM)	8					
		- 10 -					
		- 12 -					
		- 14					



	HAND AUG	GER BORIN	iG LO	G				
PROJECT	Suburban Pipeline Project - Phase II Manatee County, Florida	CLIENT:  Manatee County  WATER TABLE:  DATE:						
TECHNIC	Project No.: DES 096393	DATE:		7.4'	COMPLET	11/17/09 FION DEPTH:		
LOCATIO	J.R. N: See Plate I-J	TEST N	IUMBER	/17/09 <b>₹:</b>	HA2-16	8.0'		
ELEV. (FT)	DESCRIPTION	DEPTH (FT)	SYMBOL		REMAR	ks		
	Brownish-gray Fine SAND with some roots (SP)	0	6	**************************************				
	Light brown Fine SAND (SP)	- 2 -		*************		•		
	Light brown clayey Fine SAND with light orange veins (SC)	4 -						
	Light brown Fine SAND (SP)							
	Tan Fine SAND (SP)	- 6 -		And the state of t				
		8 -						
		- 10 -						
de esta de la composição de la composiçã		- 12 -						
And the second s								
		- 14 -						



	HAND AUGER	BORIN	G LO	G		
PROJEC	Suburban Pipeline Project - Phase II	CLIENT		Manate	e County	
	Manatee County, Florida Project No.: DES 096393	WATER	TABLE	6.3'		DATE: 11/17/09
TECHNIC	CIAN: J.R.	DATE:	11/	17/09	COMPLET	ION DEPTH: 8.0'
LOCATIO	ON: See Plate I-I	TEST N	UMBER	:	2-17	
	See Flate I-I		7	177	2-11	na ann an Aire ag ann an ann an Aire ag Aire an Aire a
ELEV. (FT)	DESCRIPTION	DEPTH (FT)	SYMBOL		REMAR	<b>&lt;</b> S
	Dark brownish-gray Fine SAND with some roots (SP)	0				
	Light brown Fine SAND (SP)					
	Light brown Fine SAND with some shell fragments (SP)	2 -	7: V: V: 7: V: V: 7: V: V: 7: V: V: 10: V: V:			
		- 4 -				
	Light brown Fine SAND with thin seams of dark brown Fine SAND (SP) Light brown Fine SAND	6 -	V. V. S			
	with abundant shell fragments (SP)		\$ \p\ \p\ \q			
	Light grayish-brown Fine SAND (SP)	- 8 -				
		- 10 -				
		- 12 -				
		- 14 -			ENVO	



HAND AUGER BORING LOG									
PROJEC	T: Suburban Pipeline Project - Phase II	CLIENT	CLIENT:  Manatee County						
	Manatee County, Florida Project No.: DES 096393	1	R TABLE	<b>፤:</b> 7.2'	<b>DATE:</b> 11/1	7 <u>/09</u>			
TECHNIC	CIAN: M.M.	DATE:	11/	/17/09 CO	MPLETION DEPTH: 8.0'				
LOCATIO	ON:	TEST N	IUMBER	₹:					
	See Plate I-K	T	TZ	HA2-18	3				
ELEV. (FT)	DESCRIPTION	DEPTH (FT)	SYMBOL	F	REMARKS				
	Grayish-brown Fine SAND	0	( 1/4 2):		character and the second				
	with some roots (SP)		1 × 1 × 1						
	Light gray Fine SAND (SP)								
	Brown Fine SAND (SP)								
	Light brown Fine SAND (SP)	_ 2 -							
			3:171:121:						
	Light brown silty, slightly clayey Fine SAND with light orange veins (SM)	_ 4 -							
	Light brown Fine SAND (SP)								
	i								
	i		k::::;:						
ŀ	Tan Fine SAND	<del> </del> 6 -							
	with abundant shell fragments (SP)		∇. ∇. \						
	with abundant shell hagments (Or )		\.\dot						
		_	γマ : σ:						
	Light brownish-gray Fine SAND		♡. ♡ .♥						
1	with shell fragments (SP)	8 -	<u> </u>						
						I			
		- 10 -	and our statement of the contract of the contr						
i i									
- Control of the Cont									
and the state of t		12 -							
enter transaction									
and the same of th									
		14 -							
1			1						



	HAND AUGE	R BORIN	G LO	G		
PROJEC	Γ: Suburban Pipeline Project - Phase ΙΙ	CLIENT	:	Manate	e County	
	Manatee County, Florida	WATER	TABLE	7.5'	C COUNTY	DATE: 11/17/09
TECHNIC	Project No.: DES 096393	DATE:	11/	17/09	COMPLET	ION DEPTH: 8.0'
LOCATIO	J.R. N:	TEST N	UMBER	2:	0.40	0.0
	See Plate I-L	<del></del>		HA	2-19	-
ELEV. (FT)	DESCRIPTION	DEPTH (FT)	SYMBOL		REMARI	KS
	Brownish-gray Fine SAND with trace of roots (SP)	0				
	Light grayish-brown Fine SAND(SP)	2				
	Light brown Fine SAND (SP)	4 -				
	Light tan Fine SAND (SP)	6 -				
	Grayish-brown Fine SAND (SP)					
		8 -				
		- 10 -				
		- 12 -				
CACA THE STATE OF		- 14 -				
			]			



	HAND AUGI			J				
PROJECT:	Suburban Pipeline Project - Phase II	CLIENT:  Manatee County						
	Manatee County, Florida Project No.: DES 096393	WATER	RTABLE	: See "Note"	<b>DATE:</b> 11/17/09			
TECHNICIAN		DATE:			COMPLETION DEPTH:			
LOCATION:	M.M.	TEST	11/ IUMBER	17/09 ::	8.0'			
	See Plate I-N		<del></del>	HA	\2-20			
ELEV. (FT)	DESCRIPTION	DEPTH (FT)	SYMBOL		REMARKS			
	Grayish-brown Fine SAND with trace of roots (SP)	0						
	Mottled light brown and tan Fine SAND (SP)	2						
	Brown slightly silty Fine SAND (SP-SM)	4						
	Brown Fine SAND (SP)	6						
	Light brown Fine SAND (SP)							
<b>\</b>	Tan Fine SAND with abundant shell fragments (SP)	- 8	\(\forall \); \		ter Table not encountered ithin depth of 8.0'.			
		- 10 -						
		12						
			description of the second seco					
		- 14 -						



		ER BORING LOG	
PROJECT	T: Suburban Pipeline Project - Phase II	CLIENT:	Manatee County
	Manatee County, Florida Project No.: DES 096393	WATER TABLE:	.3' DATE:
TECHNIC	CIAN:	DATE:	COMPLETION DEPTH:
LOCATIO	J.R.	11/17/09 TEST NUMBER:	8.0'
	See Plate I-N		HA2-21
ELEV. (FT)	DESCRIPTION	DEPTH OR WAS	REMARKS
	Grayish-brown Fine SAND with trace of roots (SP)  Brown silty, slightly clayey Fine SAND (SM)  Light brown Fine SAND (SP)	2 - 2 - 4 - 2 - 2 - 2 - 2 - 2 - 2 - 2 -	·
	Tan Fine SAND (SP)	6	
		- 12 -	



	HAND AUGI	ER BORIT	√G LO	G		astanuumakaastii ja kuli kuoli kuoli ka kirikki elektrisi kirili kuuli kuulikaasta kantasta ja ja <u>massa ya</u> ja
PROJEC	Suburban Pipeline Project - Phase II Manatee County, Florida	CLIEN WATER	T: R TABLI	E:	natee County	DATE:
TECHNIC	Project No.: DES 096393  IAN:  J.R.	DATE:	11	6.9' /17/09	COMPLET	11/17/09 TION DEPTH: 8.0'
LOCATIO	OCATION: See Plate I-M			₹:	HA2-22	0.0
ELEV. (FT)	DESCRIPTION	DEPTH (FT)	SYMBOL		REMAR	ĸs
	Brownish-gray Fine SAND with trace of roots (SP)	0	<b>8</b>		MP-45 UST TO THE TOTAL OF THE BUILDING AND A	
	Light brown Fine SAND (SP)	2				
	Light brownish-gray slightly clayey Fine SAND (SP-SM)		7 7 7 7 7 7 7 7 7 7 7 7	,		
	Tan Fine SAND (SP)	4				
	Tan Fine SAND with abundant shell fragments (SP)	- 6	. □ . □ . □ . □ . □ . □ . □ . □ . □ . □			
		8				
		- 10 -	- Advantage representation of the second repr			
		12 -				
		- 14 -				



	HAND AUGE	R BORIN	G LOC	G
PROJEC	Suburban Pipeline Project - Phase II Manatee County, Florida	CLIENT	: TABLE	Manatee County E: DATE:
TECHNIC	Project No.: DES 096393	DATE:		7.3' 11/17/09 COMPLETION DEPTH:
LOCATIO	M.M.	TEST N	11/ UMBER	/17/09 8.0' <b>₹:</b>
	See Plate I-O		T .	HA2-23
ELEV. (FT)	DESCRIPTION	DEPTH (FT)	SYMBOL	REMARKS
	Brown Fine SAND with trace of roots (SP)	0		
THE	Mottled brown and gray Fine SAND with trace of cemented sand (SP)	- 2 -		
	Dark brown clayey Fine SAND (SC)			
	Light brownish-gray CLAY with seams of brown Fine SAND (CH/SP)	4		
	Light brownish-gray clayey Fine SAND with trace of roots (SC)	6 -		
	Light brown Fine SAND (SP)			
		8 -		
		- 10 -		
		- 12		
my de la constitución de la cons				
SECTION AND ADDRESS OF THE PROPERTY OF THE PRO		14 -		



	HAND AUGEI	R BORIN	G LOC	) B					
PROJEC	T: Suburban Pipeline Project - Phase II	CLIENT:  Manatee County							
	Manatee County, Florida Project No.: DES 096393	WATER	TABLE	7.4'	<b>DATE:</b> 11/17/09				
TECHNIC	CIAN: J.R.	DATE: COMPLETION DEPTH: 8.0'							
LOCATIO	DN: See Plate I-P	TEST NUMBER: HA2-24							
ELEV. (FT)	DESCRIPTION	DEPTH (FT)	SYMBOL		REMARKS				
The state of the s	Dark grayish-brown Fine SAND with some roots (SP)	0							
STORENSTONE STATE	Brown Fine SAND (SP)								
SHAGAFATA WADDOURFAC	Light brown and brown clayey Fine SAND (SC)	2							
	Tannish-brown slightly silty Fine SAND (SP-SM)								
	Brown and light brown Fine SAND (SP)	4 -							
	Tan Fine SAND (SP)	6							
		8 -							
		- 10 -							
The state of the s									
		- 12 -							
RANGE CONTROL OF THE									
FFE TO THE TOTAL T		- 14 -							



PROJEC	HAND AUG	CLIEN"		_		
CHICAGO CONTRACTOR CON	Suburban Pipeline Project - Phase II Manatee County, Florida Project No.: DES 096393		R TABLE	<b>:</b> :	ee County	DATE:
TECHNIC	CIAN:	DATE:		See "Note"	COMPLET	11/17/09 ION DEPTH:
LOCATION		TEST N	UMBER			8.0'
	See Plate I-P		T	T HA	2-25	and the second s
ELEV. (FT)	DESCRIPTION	DEPTH (FT)	SYMBOL		REMAR	<b>KS</b>
And the state of t	Brownish-gray Fine SAND with trace of roots (SP)	0				
	Brownish-gray Fine SAND (SP)	2				
PACHEFICORE STREET						
	Light gray Fine SAND (SP)					
	Dark reddish-brown Fine SAND (SP)	4				
	Dark brown Fine SAND (SP)	- 6				
		8 -			ter Table n thin depth	ot encountered of 8.0'.
		- 10 -				
		- 12 -				
		12				
		14 -	**************************************			



	HAND AUGE	R BORIN	ig Loc	3	endamenta anticipato processora de la constanta de la constanta de la constanta de la constanta de la constant	
PROJEC	T: Suburban Pipeline Project - Phase II	CLIEN	r:	Monato	e County	
wittenester.	Manatee County, Florida Project No.: DES 096393	WATER	RTABLE	7.9'	e County	DATE: 11/30/09
TECHNIC	CIAN:	DATE:	11/	30/09	COMPLET	ION DEPTH:
LOCATIO		TEST	IUMBER			8.0'
	See Plate I-R	T		HA	2-26	THE PROPERTY OF THE PROPERTY O
ELEV. (FT)	DESCRIPTION	DEPTH (FT)	SYMBOL		REMARI	<s< td=""></s<>
	Tan and light brown Fine SAND with trace of roots (SP)	- 2	, , , , , , , , , , , , , , , , , , ,			
	Dark brown slightly silty Fine SAND (SP-SM)	- 4				
	Brown and light brown Fine SAND(SP)					
	Tan and light brown Fine SAND(SP)	6 -				
		8 -				
		- 10 -				
		12 -				
		- 14 -				ACTION AND ACTION AND ACTION AND ACTION AND ACTION AND ACTION ACTION AND ACTION AND ACTION AC



	HAND AUGE	R BORII	IG LO	G	(A)	
PROJEC	CT: Suburban Pipeline Project - Phase II Manatee County, Florida Project No.: DES 096393	CLIEN	T: R TABLI	Ξ:	e County	DATE: 11/30/09
TECHNI	CIAN: M.B.	DATE:	11.	7.9' /30/09	COMPLET	ION DEPTH: 8.0'
LOCATION	ON: See Plate I-Q	TEST	IUMBEI	₹:	2-27	
ELEV. (FT)	DESCRIPTION	DEPTH (FT)	SYMBOL		REMARI	<b>K</b> S
	Dark brown Fine SAND with roots and trace of finely divided organic material (SP) Light grayish-brown Fine SAND with trace of roots (SP)  Tan silty Fine SAND with cemented sand fragments (SM)  Tan clayey Fine SAND (SC) Tan Fine SAND with shell fragments (SP)  Tan Fine SAND with shell fragments and trace of cemented sand fragments (SP)  Light gray Fine SAND (SP)	- 2 - 4 - 8 - 10 - 12 - 14 - 14 - 14 - 14 - 14 - 14 - 14				



	HAND AUGE	R BORIN	ig Log			
PROJEC	Suburban Pipeline Project - Phase II	CLIENT		Manate	e County	
	Manatee County, Florida Project No.: DES 096393	WATER	R TABLE:	6.9'		DATE: 11/30/09
TECHNIC	CIAN:	DATE:	11/2		COMPLET	TION DEPTH: 8.0'
LOCATIO	M.B.	TEST N	11/3 IUMBER:		L	0.0
	See Plate I-S	<del></del>	Т, Т	<u>HA</u>	2-28	
ELEV. (FT)	DESCRIPTION	DEPTH (FT)	SYMBOL		REMARI	KS
	Gray Fine SAND with roots (SP)	0				
	Light gray Fine SAND (SP)  Brown Fine SAND (SP)					
	Brown and light brown silty, slightly clayey Fine SAND(SM)	- 2 -				
	Light brown slightly silty, slightly clayey Fine SAND (SP-SM)		7.7.7 7.17.7.1 7.17.17.1			
	Light brown Fine SAND with shell fragments (SP)	4 -				
	Tan and light brown Fine SAND (SP)					
	Light tan and light brown Fine SAND with trace of shell fragments (SP)	- 6	▽			
	Light brown Fine SAND with shell fragments (SP)					
		8 -	\$ . \(\frac{1}{2} \). \(\frac{1}{2} \).			
			The state of the s			
		10 -				
		10	and the state of t			
		- 12 -				
		14 -				



### HAND AUGER BORING LOG CLIENT: PROJECT: Suburban Pipeline Project - Phase II Manatee County Manatee County, Florida Project No.: DES 096393 WATER TABLE: DATE: 11/30/09 COMPLETION DEPTH: DATE: TECHNICIAN: M.B. 11/30/09 TEST NUMBER: LOCATION: HA2-29 See Plate I-T SYMBOL ELEV. DEPTH DESCRIPTION REMARKS (FT) (FT) Dark brown and light gray Fine SAND (SP) Light tan Fine SAND (SP) Brown silty, slightly clayey Fine SAND 2 Light brown Fine SAND (SP) Tan Fine SAND with shell fragments (SP) Light gray Fine SAND with trace of shell fragments (SP) 6 Gray Fine SAND with shell fragments (SP) 10 12 14



	HAND AUGER	BORIN	G LOC			
PROJEC	T: Suburban Pipeline Project - Phase II	CLIENT	:	Manata	e County	
	Manatee County, Florida Project No.: DES 096393	WATER	TABLE	6.3'	e County	DATE: 11/30/09
TECHNIC	S.F.	DATE:	11/:	30/09	COMPLET	ION DEPTH: 8.0'
LOCATIO	N: See Plate I-AA	TEST N	UMBER	:	2-30	
			9			
ELEV. (FT)	DESCRIPTION	DEPTH (FT)	SYMBOL		REMARI	<s< td=""></s<>
	Dark gray and brown Fine SAND with roots (SP)	0				
	Cross and tan alightly aith;		: :\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\			
	Gray and tan slightly silty, slightly clayey Fine SAND (SP-SM)	- 2 -	* V			
			1 7 7 1 7 7 7 1 7 7 7 1			
	Tan and light gray Fine SAND with brown veins (SP)	4 -				
		- 6 -				
		- 8 -				
		- 10 -				
		- 12 -				
		- 14 -				



## DRIGGERS ENGINEERING SERVICES INCORPORATED

	HAND AUGE	ER BORIN	G LO	G				
PROJEC	T: Suburban Pipeline Project - Phase II	CLIENT	,	Mana	tee County	William Control of the Control of th		
	Manatee County, Florida Project No.: DES 096393	WATER	TABLE	5.3'	ico oourny	DATE: 11/30/09		
TECHNIC	CIAN: S.F.	DATE:	111	30/09	COMPLETI	ON DEPTH: 8.0'		
LOCATIO	DN:	TEST N	UMBER	2:	HA2-31			
	See Plate I-T		4		AZ-31			
ELEV. (FT)	DESCRIPTION	DEPTH (FT)	SYMBOL		REMAR	<b>(S</b>		
	Dark brown and gray slightly silty Fine SAND with roots (SP-SM) Brown slightly silty Fine SAND with rock and shell fragments (SP-SM) Orangish-brown Fine SAND with trace of shell fragments (SP) Light tan Fine SAND (SP)  Brown silty, slightly clayey Fine SAND (SM) Tan Fine SAND with trace of shell fragments (SP)	0 - 2 - 4 - 6 - 10 - 12 - 14 - 14 - 14 - 14 - 14 - 14 - 14						
i		1						



	HAND AUGE	R BORIN	iG LOC	ì		
PROJEC	T: Suburban Pipeline Project - Phase II	CLIENT	Γ:	Manate	e County	
	Manatee County, Florida Project No.: DES 096393	WATER	RTABLE	6.0'	Courty	DATE: 11/30/09
TECHNIC	CIAN: S.F.	DATE:	11/3	30/09	COMPLET	ON DEPTH: 8.0'
LOCATIO	ON: See Plate I-S	TEST N	UMBER	•	2-32	
		DEPTH	9			<del>- 1900 de la la la descripción de la constante de la constant</del>
ELEV. (FT)	DESCRIPTION	(FT)	SYMBOL		REMAR	«S
	Dark gray slightly organic Fine SAND with roots (SP)	0				
	Gray Fine SAND (SP)					
	Dark brown slightly silty Fine SAND (SP-SM)		unitt Guirti			
	Brown Fine SAND (SP)	2				
	**	- 4 -				
	Dark brown slightly silty Fine SAND		):4:t()			
	(SP-SM)					
	Gray and tan Fine SAND (SP)					
		- 6 -				
		- 8 -				
and the second s		- 10 -				
		- 10				
		- 12 -				
		- 14 -				



PROJECT:		CLIEN	T:						
	Suburban Pipeline Project - Phase II Manatee County, Florida Project No.: DES 096393	WATER TABLE:  4.9'  Manatee County  DATE:							
TECHNICIAN	•	DATE:	12	4/09	COMPLETION DEPTH: 8.0'				
LOCATION:	J.D.	TEST	NUMBER	÷105					
	See Plate I-U		HA2-33						
ELEV. (FT)	DESCRIPTION	DEPTH (FT)	SYMBOL		REMARKS				
	Dark brown Fine SAND with trace of roots (SP)	0	N::/						
	Light brown Fine SAND with shell (SP)								
	Gray Fine SAND (SP)								
	Dark brown Fine SAND		w. m p . m						
	with finely divided organic material (SP)	- 2							
	Brown slightly silty Fine SAND (SP-SM)								
	Light brown Fine SAND (SP)								
		4							
	Brown Fine SAND (SP)								
		- 6							
	Very light grayish-brown Fine SAND (SP)								
		8	* * * * * * * * * * * * * * * * * * * *						
		10							
esana per del repete d									
		- 12	-						
And the control of th									
		14							



	HAND AUG			G.				
PROJECT:	Suburban Pipeline Project - Phase II  Manatee County, Florida	CLIENT	Γ: R TABLE		ee County	DATE: 12/4/09		
TECHNICIAN	Project No.: DES 096393	DATE:		5.9'	COMPLET	TON DEPTH:		
LOCATION:	J.D.	12/4/09 8.0' TEST NUMBER:						
	See Plate I-U		T	H <i>A</i>	\2-34			
ELEV. (FT)	DESCRIPTION	DEPTH (FT)	SYMBOL		REMAR	KS		
	Grayish-brown Fine SAND with roots (SP)	0						
SOCIAL PROPERTY AND A STATE OF THE STATE OF	Gray Fine SAND (SP)							
The control of the co	Light gray Fine SAND (SP)							
nico e e e e e e e e e e e e e e e e e e e		2						
	Dark brown Fine SAND with finely divided organic material		200 1 200 200 200 200 200 200 200 200 20					
	(SP) Dark reddish-brown Fine SAND (SP)	4						
		- 6						
	Dark brown slightly silty Fine SAND (SP-SM)							
		8						
		- 10						
ALL REPORT OF THE PROPERTY OF								
		12						
ROBERT CONTRACTOR CONT		1 4						
		14						



	H	AND AUGER BO	RING	LOC	Š				
PROJEC	T: Cubushan Dingling Project - Phone II	CL	ENT:		8.6	- 0			
PARTITION OF THE PARTIT	Suburban Pipeline Project - Phase II Manatee County, Florida Project No.: DES 096393			ABLE	7.3'	e County	DATE: 12/4/09		
TECHNIC	CIAN: J.D.	DA	TE:	12/	4/09	COMPLET	ION DEPTH: 8.0'		
LOCATIO	DN:	TE	ST NUI	MBER		2.25	0.0		
	See Plate I-AA		HA2-35						
ELEV. (FT)	DESCRIPTION	DEF (F	Γ)	SYMBOL		REMARI	KS		
	Dark grayish-brown slightly s Fine SAND with trace of roo and gravel (SP-SM) Gray Fine SAND with trace of (SP)	ots		OK-P					
	Dark brown Fine SAND with finely divided organic mat (SP)		7						
	Reddish-brown Fine SAND(	SP) 4							
	Light brown Fine SAND (S	P)							
		8							
		10	) -						
		- 12	! -						
		- 14							



PROJECT:		CLIENT:							
	Suburban Pipeline Project - Phase II  Manatee County, Florida	WATEI	R TABLE:	<u>Ma</u>	anatee County	DATE:			
	Project No.: DES 096393			6.9'	- CORDI F	12/4/09			
TECHNICIAN:	; J.D.	DATE:	12/4/0	19	COMPLE	TION DEPTH: 8.0'			
LOCATION:		TEST	NUMBER:	<u> </u>					
	See Plate I-AA	1	T	***************************************	HA2-36				
ELEV. (FT)	DESCRIPTION	DEPTH (FT)	SYMBOL		REMAR	≀KS			
	Dark brown Fine SAND with roots (SP)	0	~/						
	Gray Fine SAND (SP)								
	•								
No.			1:::::						
-	Dark brown Fine SAND with roots								
	and finely divided organic material	- 2	25.53						
h	(SP)								
	Brown to light brown Fine SAND (SP)		4:::::						
	Light brown Fine SAND (SP)		J						
	<del></del>		J						
		A	]::::::						
		4 -	↑.::::::						
	Brown Fine SAND (SP)	-	<del>       </del>						
	DIOWILL INC O. A.C.	-	<b>∤</b> ∷∷∷}						
			<b>.</b>						
		6 -							
			<b>[</b> ]						
			†::::::1						
			\:::::						
		→ 8 -							
			1						
			]						
		10	1						
		10 -	1						
			1						
a reproductive			1						
			-						
		12 -							
		. –							
			1						
			1						
			1						
1		- 14 -	1						



ROJECT:		CLIENT:			
	Suburban Pipeline Project - Phase II Manatee County, Florida Project No.: DES 096393	WATER	<b>TABLE:</b> 5.9'	Manatee County	DATE: 12/4/09
ECHNICIAN:		DATE:		COMPLE	TION DEPTH:
OCATION:	J.D.	TEST NU	12/4/09 JMBER:	1140.07	8.0'
	See Plate I-W			HA2-37	
ELEV. (FT)	DESCRIPTION	DEPTH (FT)	SYMBOL	REMAI	RKS
	Gray and brown Fine SAND with roots (SP)	0	7. N. S.	AN AMERICA AND AN APPEARANT MANAGEMENT CHAMBOOK ESTABLISHED AND SERVICE OF THE SE	
	Gray Fine SAND (SP)				
	Dark brown Fine SAND		0 1 10 10 10 10 10 10 10 10 10 10 10 10		
Table 10 (10 (10 (10 (10 (10 (10 (10 (10 (10	with finely divided organic material (SP)	2			
1	Brown Fine SAND (SP)	:			
	Light brown Fine SAND (SP)	:			
		4			
	Very light grayish-brown Fine SAND	6			
	(SP)				
		8			
			T for the second		
TO THE OWNER OF THE OWNER OF THE OWNER OF THE OWNER OW		10			
		10			
		12			
		-			
		14 -			



	HAND AUGE	R BORIN	IG LO	G		
PROJEC	T: Suburban Pipeline Project - Phase II	CLIEN	Γ:	Manata	ee County	
	Manatee County, Florida Project No.: DES 096393	WATER	RTABLE	######################################	se County	DATE: 12/4/09
TECHNIC	CIAN: J.D.	DATE:	12	2/4/09	COMPLET	ION DEPTH: 8.0'
LOCATIO	ON: See Plate I-V	TEST	IUMBEF	₹:	\2-38	
	See Flate I-V		占	11/2	12-30	
ELEV. (FT)	DESCRIPTION	DEPTH (FT)	SYMBOL		REMAR	KS
	Dark grayish-brown Fine SAND with roots (SP)	0	7 1/3/2 70 1/3/2 17 1/3/2			
	Gray Fine SAND (SP)					
	Dark brown Fine SAND with trace of finely divided organic material (SP)	2				
	Light brown Fine SAND with trace of roots (SP)					
		4		4		
	Orangish-brown slightly silty Fine SAND (SP-SM)					
	Very light grayish-brown Fine SAND (SP)	6				
		8 -				
			Supplementary of the control of the			
		10 -				
- The state of the		- 12 -				
		- 14 -				



	HAND AUGE	R BORIN	IG LOC	·		
PROJECT	C. A. A. D. C. D. Chara. Dhana B.	CLIEN	Г:	h # i -	<u> </u>	
	Suburban Pipeline Project - Phase II Manatee County, Florida Project No.: DES 096393	1	R TABLE:	Manate : 3.5'	e County	DATE: 12/4/09
TECHNICI	AN: J.D.	DATE:	12/	4/09	COMPLET	ION DEPTH: 8.0'
LOCATION	√:	TEST N	IUMBER:			0.0
	See Plate I-V	т!		HA	2-39	
ELEV. (FT)	DESCRIPTION	DEPTH (FT)	SYMBOL		REMAR	KS
	Dark gray Fine SAND with roots (SP)	0	7. / - / - / 2/			ACCESS AND
	Grayish-brown Fine SAND (SP)					
	Brown Fine SAND (SP)	2				
	Light brown Fine SAND (SP)	6 -				
		- 12 -				



PROJEC	HAND AUG	CLIENT		
,,,,,,,	Suburban Pipeline Project - Phase II			Manatee County
	Manatee County, Florida Project No.: DES 096393		<b>R TABLE:</b> 5.5'	<b>DATE:</b> 12/4/09
TECHNIC	CIAN: J.D.	DATE:	12/4/09	COMPLETION DEPTH: 8.0'
LOCATIO	ON:	TEST	NUMBER:	
	See Plate I-W		T T	HA2-40
ELEV. (FT)	DESCRIPTION	DEPTH (FT)	SYMBOL	REMARKS
	Dark gray Fine SAND with roots and finely divided organic material (SP)	0	5 2 5 2 5 2 5 2 5 2 5 2 5 2 5 2 5 2 5 2	
İ	Gray Fine SAND (SP)			
ı	Light gray Fine SAND (SP)			
	Dark brown slightly silty Fine SAND with finely divided organic material	2		
	(SP-SM)			
	Brown Fine SAND (SP)	- 4 -		
	Light brown Fine SAND (SP)			
	Very light grayish-brown Fine SAND (SP)			
		- 6 -		
		8 -		
		- 10 -		
TOTAL PROPERTY OF THE PARTY OF		- 12 -		
		14 -		



	HAND AUGE	R BORIN	iG LOG			aan sootee ey ayyaayaa ka ah
PROJEC	T: Suburban Pipeline Project - Phase II	CLIENT	Γ:	Manata	e County	
	Manatee County, Florida	WATER	R TABLE:		County	DATE:
TECHNIC		DATE:	10/	3.3' 4/09	COMPLET	12/4/09 ION DEPTH:
LOCATIO	J.D.	TEST	IUMBER:	:		8.0'
	See Plate i-BB	7		HA:	2-41	
ELEV. (FT)	DESCRIPTION	DEPTH (FT)	SYMBOL		REMARI	KS
	Grayish-brown Fine SAND	0				
	with trace of roots (SP) Light brown Fine SAND with shell (SP)		7.:∀.:∀:			
	Gray Fine SAND (SP)	-				
	Gray Fine Or (ND (CF)					
	5 - CAND (OD)	- 2		-		
	Brown Fine SAND (SP)					
	Orangish-brown clayey Fine SAND (SC)					
	Light brown slightly silty Fine SAND	4 -	4.4.			
	with shell (SP-SM)					
	Very light grayish-brown Fine SAND					
	(SP)					
	(31)	6 -				
	Brown Fine SAND (SP)					
		8 -				
		10 -				
						Acceptance of the control of the con
		12 -				
		12				
						hacentivise
						consumerities
		14 -				DOMANISH



probability of the probability o	HAND AUGE	R BORII	VG LO	G		
PROJEC	CT: Suburban Pipeline Project - Phase II	CLIEN.	T:	Manata	- County	
NCH SALES STOCKES	Manatee County, Florida Project No.: DES 096393		R TABLE	Manate E: 3.9'	ee County	DATE: 12/4/09
TECHNIC	CIAN: J.D.	DATE:		2/4/09	COMPLET	ION DEPTH: 8.0'
LOCATIO	ON:	TEST	NUMBER	₹:		0.0
	See Plate I-CC		Т	T HA	2-42	
ELEV. (FT)	DESCRIPTION	DEPTH (FT)	SYMBOL		REMARI	ks
The secretaries and secretarie	Dark gray slightly silty Fine SAND with trace of roots and gravel (SP-SM)	0	1.05 1.7.6	The state of the s	CONTRACTOR OF THE PROPERTY OF	
No. of the Control of	Grayish-brown Fine SAND with Crushed Limestone and pieces of asphalt (SP)		0 .0 .0 .0 .0 .0 .0 .0 .0 .0 .0 .0 .0 .0	1 4 6 mm P 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1		
<b>BEFFFFFFFFFFFFFFFFFFFFFFFFFFFFFFFFFFFF</b>	Gray Fine SAND (SP)	2				
COMPANION STATEMENT OF THE STATEMENT OF	Dark brown slightly silty Fine SAND (SP-SM)			The state of the s		
	Orangish-brown clayey Fine SAND (SC)	- 4	1//			
Nedjaka jirkeziya karaneka	Light tan cemented Fine SAND and shell (SP)					
Toward Commence of the Commenc	Light brown Fine SAND with shell (SP)	6	\(\nabla \). \(\nabla \). \(\nabla \). \(\nabla \).	A regular to the second		
Antique de la constante de la	Light grayish-brown Fine SAND with trace of shell (SP)					
Manage of the control		8 -				
And and a second						
A Commission of the Commission						
		- 10 -				
		- 12 -				
		14 -	The state of the s			

SUMMARY OF LABORATORY TEST RESULTS Driggers Engineering Services Incorporated

## Page 1 of 2

BORING	DEPTH	DESCRIPTION	% M	. ∀ d	ຶ້	ATTE	ATTERBERG LIMITS	4. q	v.c.	CON	G.S.	ORG	Hď		so 4	RES.	
	(11)			 ()		TI II	PL SL	(fg)				(%)		(mdd)	(mdd)	(Ohm-cm)	
HA-2-2	3.0' - 4.3'	Brownish-gray slightly silty Fine SAND with shell and limestone fragments									*						7
HA-2-4	3.9' - 6.2'	Grayish-brown silty, slightly clayey Fine SAND									*						Т
HA-2-5	2.0' - 4.5'	Brown Fine SAND									*		6.3	38.9	09	17,000	Т
HA-2-7	1.8' - 3.3'	Very dark brown organic slightly silty Fine SAND										6:11					Т
HA-2-8	3,1' - 4,2'	Mottled grayish-brown Find SAND									*						T
HA-2-9	4.5' - 5.7'	Very dark brown organic Fine SAND with trace roots										9.7				THE PARTY OF THE P	T
HA-2-10	3.0' - 4.7'	Very dark brown slightly organic Find SAND							·			3.9				Petersional particular and particular delicable belonging	T
HA-2-11	4.0' - 6.0'	Dark brown slightly silty Fine SAND with finely divided organic material									*	1.2					T
HA-2-12	1.0' - 3.5'	Tan Fine SAND									*					A CONTRACTOR OF THE PROPERTY O	Ţ .
HA-2-14	1.0' - 2.5'	Tan Fine SAND with limestone fragments									*						Т—
HA-2-16	3.0' - 4.0'	Light brown clayey Fine SAND with light orange veins	8.8			82	20				*						Τ
HA-2-18	3.7' - 4.3'	Light brown sity, slightly clayey Fine SAND with light orange veins	7.6			NP	N P				*						1
HA-2-20	4.0' - 5.2'	Brown slightly silty Fine SAND									*		6.5	51.6	78	3,400	Т-
HA-2-21	0.0' - 3.5'	Grayish-brown Fine SAND with trace roots									*						Т
HA-2-23	4.5' - 6.3'	Light brownish-gray clayey Fine SAND with trace roots	16.3			25	=				*					arkönterryksissä kalanda kalan	Т
HA-2-26	0.0' - 3.7'	Light tan and brown Fine SAND with trace roots									*					resembly refer to the first of	T
HA-2-27	0,0' - 0,8'	Dark brown Fine SAND with trace finely divided organic material and roots										2.9					T
HA-2-27	2.8' - 4.0'	Tan silty Fine SAND with cemented sand fragments									*						
$W\%$ = $Y_d(pcf)$ = $G_s$	Water Dry D Specil	Water Content  Dry Density  Specific Gravity  ORG. (%)	11 11 11	రి రీ ర్	Consolidation Test Grainsize Analysis Organic Content	on Test analysis (	Consolidation Test Grainsize Analysis (Hydrometer) Organic Content	ter)	CF	CLIENT:	Σ	anatee (	County (	Manatee County Government	lent		1
11 11 11	Liquik Plastik Shrink		11 11 11	To Ta	Total Chloride Total Sulfate Lab Resistivity	ide te vity			PRO	PROJECT:	Su	Suburban Pipeline, Phase II Manatee County, Florida	ípeline, T unty, Flo	<sup>o</sup> hase II rida			
P.P. (tsf) = U.C. =	Pocke Uncor	Pocket Penetrometer * Unconfined Compression **	11 11	Se	See Test Curves Percent Passing	urves ssing No.	See Test Curves Percent Passing No. 200 Sieve	4)	E E	<u>ب</u>	DE	DES 096393	2				
																	4


SUMMARY OF LABORATORY TEST RESULTS

# SUMMARY OF LABORATORY TEST RESULTS


BORING	DEPTH	DESCRIPTION	% M	P \	*9	ATTERBERG	ERG S	P.P.	U.C.	CON	G.S.	ORG	Hd	-	so 4	RES.
	(11)			(lad)		UL PL	SI	(ts1)				<u> </u>		(mdd)	(mdd)	(Ohm-cm)
HA-2-28	3.0' - 3.8'	Light brown slightly silty, slightly clayey Fine SAND									*		6.3	42.2	45	8,400
HA-2-30	4.0' ~ 8.0'	Tan and light gray Fine SAND with brown veins									*					entry indeptation of the content of
HA-2-31	1,0' - 3.5'	Light tan Fine SAND									*					A PROPERTY OF THE PROPERTY OF
HA-2-33	2.5' - 4.5'	Light brown Fine SAND									*					
HA-2-35	2.4' - 3.0'	Dark brown Fine SAND with finely divided organic material									*					
HA-2-36	1.7' - 2.3'	Dark brown Fine SAND with roots and finely divided organic material										3.3				
HA-2-38	1.5' - 2.5'	Dark brown Fine SAND with trace finely divided organic material									*	1.7				
HA-2-39	3.0' - 4.8'	Light brown Fine SAND									*		0.9	63.1	54	27,500
HA-2-40	2.5' - 3.6'	Dark brown Fine SAND with finely divided organic material										2.1				
HA-2-41	2.8' - 4.0'	Orangish-brown clayey Fine SAND	27.7			37 18					*					
						-										
		Ħ	IJ	ŭ	Consolidation Test	on Test			CLIENT:	Ž	Ma	natee C	ounty C	Manatee County Government	ıent	
$Y_d(pcf) = G_s$		λ.	11 11	ÖÖ	Grainsize Analys Organic Content	Grainsize Analysis (Hydrometer) Organic Content	drometer)						•			
TT =		Liquid Limit Cl. (ppm)	II	Ĕ	Total Chloride	ide			PROJECT:	ECT:	Sub	Suburban Pipeline, Phase II	peline, P	hase II		
PL s		Plastic Limit SO <sub>4</sub> (ppm)		Ĕ.	Total Sulfate	9					Mai	Manatee County, Florida	ınty, Floı	rida		
(tst)		NES. (OHIII-CHI) Pocket Penetrometer *		ĭ ŏ	Lab Resistivity See Test Curves	villy					DE	DES 096393				
U.C. =		Unconfined Compression **	Į\$	S &	ercent Pas	Percent Passing No. 200 Sieve	) Sieve		H. H. A. A.		7					Page 2 of 2

**GRAINSIZE ANALYSES** Driggers Engineering Services Incorporated


DRIGGERS ENGINEERING SERVICES, INC.




DRIGGERS ENGINEERING SERVICES, INC.




DRIGGERS ENGINEERING SERVICES, INC.




DRIGGERS ENGINEERING SERVICES, INC.




DRIGGERS ENGINEERING SERVICES, INC.




DRIGGERS ENGINEERING SERVICES, INC.




## DRIGGERS ENGINEERING SERVICES, INC.




DRIGGERS ENGINEERING SERVICES, INC.




## DRIGGERS ENGINEERING SERVICES, INC.




DRIGGERS ENGINEERING SERVICES, INC.




DRIGGERS ENGINEERING SERVICES, INC.




DRIGGERS ENGINEERING SERVICES, INC.




DRIGGERS ENGINEERING SERVICES, INC.




DRIGGERS ENGINEERING SERVICES, INC.




DRIGGERS ENGINEERING SERVICES, INC.




## DAIGGERS ENGINEERING SERVICES, INC.





## DRIGGERS ENGINEERING SERVICES, INC.





DRIGGERS ENGINEERING SERVICES, INC.
























































































July 28, 2011

Permit #: 0133068-971 DSGP

Mr. Sia Mollanazar, Deputy Director Manatee County Public Works Department 1022 26<sup>th</sup> Avenue East Bradenton, Florida 34208

WATER SYSTEM: Manatee County

PROJECT NAME: Suburban System Water Line

Replacement Phase 2 - Project No. 60747.70

**EXPIRES:** July 22, 2016

## Dear Mr. Mollanazar:

Our office received the Notice of Intent to Use a General Permit for construction of the referenced water distribution system on July 22, 2011.

Please be advised that the activity must conform to the description contained in your Notice of Intent to Use a General Permit and that any deviation may subject the system to enforcement action.

Upon completion of the project, please provide us with the following:

- (1) A "Request for Letter of Release to Place Water Supply System into Service" DEP Form 62-555.900(9).
- (2) Copies of satisfactory bacteriological test results taken on two consecutive days at points indicated on approved plans. Sample locations are at end of line connections (24), end of line blowoff (1 at C31 sheet), the 6" conflict piping on C1 sheet, cut in on C29 sheet and any internal phase lines.
- (3) Pressure test results of the water system.

Following the receipt of this information we may then issue a clearance letter releasing the facilities for public use. This project may not be placed into service until a letter of clearance has been issued.

## Suburban System Water Line Replacement Phase 2

July 28, 2011 Page 2

This General Permit does not relieve the permittee of the responsibility for obtaining a Dredge and Fill Permit where it is required.

If you have any questions, please call Harry Messick at (941)748-0747, ext. 1355.

Sinceraly

Brian C. Dietz, PE

Environmental Health Services

BCD

CC:

Wayne Troxler, P.E./MCPWD

Andy Fischer/MCPWD David Schofield/MCUO

Robert A. Cannarella, P.E / CH2M Hill

File