

MAR		LENGTH		TYP S			С	D.	Ε	F		J	K	Ņ	Ø
ZE	DES	FT IN	BAR5	BAR	G	FT IN FR	FT IN FR	FT IN FR	FT IN FI	R FT I	N FR FT IN	FR FT IN FR	FT IN FR	NO	ANG
			TION			TRUCTURE					EQUIRED =				
\neg	1									T	1				
-			7.5	-	╁					+				-	-
-	51	14- 8	36	\rightarrow	┸	14-8								\Box	
5	54	8- 6	66	1		8-6				1	ļ.			-	
5	55	3-10	33	4 4	1 4	0-11	0-6			T					
\rightarrow	56	14- 8	4		+	14-8		-		†		+	1	-	_
	$\overline{}$			_	╀					+				\vdash	<u> </u>
5	59	1- 6	65	10		1-0	0- 6				- 1		1		
					T						Î				
_		LOCA	TION	SUP	-	TRUCTURE	DECK SDAM	2		NO DI	EQUIRED =	1	1		
		LUCA	1 1 014	300	- 73	INDUIDAL	DECK SPAN			NO. NO	COUINCE -	<u> </u>	1	_	
				L											
7	52	14- 8	36	1	1	14- 7 1/2									
_	54	8- 6	66		+	8-6				+					
_					+-					┼──	_		-	-	_
_	55	3-10	33	4 -	4		0- 6								
5	<i>57</i>	14- 8	4	1		14- 7 1/2									
_	59	1- 6	65	_		I- 0	0- 6			1	1	1			
-1			- 55		+					+	+	+	1	\vdash	\vdash
\perp													I		
		LUCA	TION	SUP	ERS	TRUCTURE	DECK SPAN	3		NO. RI	EQUIRED =	1			
\neg										T .					
7	53	14- 4	36	1		14- 3 1/2				 				-	<u> </u>
_				\rightarrow	+					+	_			\vdash	-
	54	8- 6	60			8-6									
5 .	\$5	3-10	30	4 4	4	0-11	0- 6							1	
\rightarrow	58	14- 4	4	_		14- 3 1/2							1	\Box	
\rightarrow	\rightarrow			_	+			—	-	+		+	1	\vdash	\vdash
5 .	59	1- 6	59	10	-	1-0	0- 6			-				\square	<u> </u>
1			LI											L ∣	L
		LUCA	TION	END	BE	NT				NO. RI	EOUIRED = .	2			
\neg		200			Ť	1				1			1		
_+				-	+-					┼				-	_
8 1	P01	6- 0	5		\perp	6-0									
4 1	P02	7- 3	4	12	1	2-11	4- 4				,				60
_	P03	8- 2	6		1	8- 2				1			1		
_					+-					+	\rightarrow		-	-	_
4	P04	3- 1	1		\perp	1-2	1-11								60
4 1	P05	3-11	1	12		1-11	2-0			1	- 1		i I		19
4 1	P06	2- 9	1	12	\top	0-10	1-11			1			1		6.
-	-				╁				1 5	+			 	\vdash	
\rightarrow	P07	6- 9	6		╀	2- 6	1- 5	1- 5	1- 5					-	
4 1	P08	5- 4	1	11		.2- 6	1-5	1- 5		1	- 1				
4	P09	5- 0	18	11	\top	2- 0	1-6	1-6				1	1		
\rightarrow	P10				+		1- 6	1-6		+			1	\vdash	\vdash
-	$\overline{}$	4-11	2		+	1-11				₩			-	\vdash	_
4	PII	6-6	2	_11		2-6	2- 0	2- 0							
8 1	P12	3-10	4	10	Т	2- 6	1- 4			T					
-					+					†			1	\vdash	\vdash
			للليليا	يلبسا							<u> </u>				L
		LDCA	TION	INT	BŁ	NT				NO. RI	EQUIRED = .	2			
T	Ī														
3. 1	POI	5-10	5	1	\top	5-10				T	1		} .	\Box	
_					1 7		1 8			1	\rightarrow				-
	P02	7- 5	7	_	7 4		1-8			+	-		 	\vdash	<u> </u>
	P03	5- 0	1	11	\perp	1-8	1-8	1-8							
4 1	P04	4-10	1	11		1-8	1- 7	1-7							
	P05		4			2- 6	1- 4	- /		+	- †	+	 	\vdash	\vdash
2-1	-03	3-10	4	10	+	2-0	J- 4			+				\vdash	<u> </u>
													1		
		LOCA	TION	APP	ROA	CH SLAB E	81			ND. RI	EQUIRED =	1			
\neg					T						I	T	1		
_+	4.		_	 , 	+-	7 -				+	-	_	 	\vdash	<u> </u>
	A1	<u>7- 8.</u>	8		4	7-8				-				\Box	<u> </u>
3 /	A2	7-8	10	1	1	7-8_									
	A3	5- 8	1	1	\top	5- 8									
_	$\overline{}$	5- 8			+	5- 8				+	+	+	 	\vdash	\vdash
_	A4		1	1	+					1			ļ	\vdash	-
5 /	A5	2-10	I	1		2-10									
9 /	A6	2-10	ī	1	T	2-10									
5 /		7-11			+-					1		_	 	\vdash	\vdash
_	_		1	1	+	7-11				+	-	+		\vdash	<u> </u>
8	A8	7-11	1	1	1	7-11_					L				L
5 /	A9	VARY	22	1	T	7- 1				1					
- +		8- 1		\rightarrow	+	9- 0				†		+	1	\vdash	\vdash
_	اا		. 0	1	+					+				$\vdash \vdash$	<u> </u>
5	A10	3- 5	22		\perp	3 - 5				\perp					
	4 4 4 1	1- 6	5	1		1- 6									
5 .	All														

MAI	RK	LENGT	Н	NO	TYP	51	TΥ		В	Ç	D	Ε	F	Н	J	· K	N	Ø
SIZE	DE5	FT I	N	BARS	BAR	Α	G	FT	IN FR	FT IN FR	FT IN FR	FT IN FR	FT IN FR	FT IN FR	FT IN FR	FT IN FR	NO	ANG
		LC	CA	TION	AP	PR	ŪΑ	CH S	SLAB E	84_			NO. REQUI	RED = 1				
		-																
5	A1	7-	8	8	1			7	'- 8									
8	A2	7-	8	10	1			7	'- 8					Ì				
5	A3	5-	9	1	- 1			5	- 9									
8	A4	5-	9	1	- 1			5	- 9									
5	A5	3-	0	- 1	1			2	-11 1/4									
8	A6	3-	0		1			2	-11 1/4					,				
5	A7	7-1	1	1	1			7	7-11									
8	AB	7-1	1	1	1			7	7-11									
5	A9	VAR	Y	22	1			7	7- 1									
		8-	1	0	1			9	1- 1					-				
5	A10	3-	5	22	1			3	5- 5		<u> </u>							
6	All	1-	6	5	- 1			1	- 6									

END OF LIST

No 65632

BRIDGE NO. 134025

				AS NOTED	l
					L
				DESIGNED BY	l.
				ABK	ł
				DRAWN BY	ľ
				CHECKED BY	L
No	REVISIONS	DATE	BY	1	ľ

CARDNO, INC.

380 PARK PLACE BLVD, SUITE 300

CLEARWATER, FLORIDA 33759

CERTIFICATE OF AUTHORIZATION 29915

DATE
4/2016

PROJECT NO.
225338

Manatee MANATEE COUNTY County PUBLIC WORKS

ANANDA BY AKELLEY NA


REBAR LIST


SHEET NO.

J:40:04 PM

11/23/2016

J:\00193\00193010.07\ms\struct\Br | 134025\B01RebarList01.dgn





BERGERON TO 65632

NO 65632

DESIGN, ENGINEER

BRIDGE NO. 134026

No. REVISIONS DATE BY AS NOTED CARDNO, I

AS NOTED CARDNO, INC.

380 PARK PLACE BLVD, SUITE 300

CLEARWATER, FLORIDA 33759

CERTIFICATE OF AUTHORIZATION 29915

DATE
4/2016

PROJECT NO.
225338

Manat
Count

Manatee MANATEE COUNTY
County PUBLIC WORKS

ANANDA B. KELLEN

FL. LICENSE NO. 65632


ELEVA TION

SHEET NO. **B2-2**


M 11/23/2016

2016

J:\00193\00193010.07\ms\struct\Br 134026\B02PlanElev02.dgn




NOTE: COMPLETE SUBSTRUCTURE WIDENING AND INSTALLATION OF TYPE K BARRIER PRIOR TO PHASE 1. TEMPORARY LANE CLOSURES PERMITTED.




PHASE 1 - CONSTRUCTION, STEP 1

- 1. SHIFT TRAFFIC LANES TO THE WEST -MAKE EACH LANE 11'-6" WIDE.
- 2. INSTALL TEMPORARY K BARRIER.
- 3. REMOVE EAST SIDE EXISTING BARRIER.
- 4. SAW CUT AND REMOVE 2'-4" TO 2'-7" OF EXISTING CONCRETE.
- 5. EXPOSE AND CLEAN EXISTING REBAR.



PHASE 1 - CONSTRUCTION, STEP 2

- 1. PLACE PROPOSED SLAB REINFORCEMENT.
- 2. POUR PROPOSED CAST IN PLACE CONCRETE SLAB UNIT.
- 3. INSTALL NEW THRIE BEAM TRAFFIC RAILING.





4:43:22 P

REMOVE EXISTING GUARDRAIL -

AFTER REMOVING THE EXISTING GUARDRAIL

BOLTS TO THE SURFACE OF THE ADJACENT

PAINT COMPOUND, THEN PATCH SURFACE.

CUT AND GRIND THE EXPOSED ANCHOR

CONCRETE, COAT WITH A ZINC-RICH

PUBLIC WORKS

Manatee MANATEE COUNTY THINANDLE KELLE

THE MICENSE NO 65632

CONSTRUCTION SEQUENCE


B2-3

SHEET

J:\00193\00193010.07\ms\struct\Br 134026\B02ConstSeg01.dgn

LEGEND

EXISTING STRUCTURE



4. SHIFT TRAFFIC LANES TO FINAL LOCATION.

€ EXISTING BRIDGE 36'-0"

SHLDR.

1'-0"

PROPOSED THRIE BEAM

12'-0"

LANE

PROPOSED (OUT TO OUT)

12'-0"

LANE

PHASE 2 - CONSTRUCTION, STEP 1

1. SHIFT TRAFFIC LANES TO THE EAST -MAKE EACH LANE 12 FEET WIDE.


2. MOVE TEMPORARY K BARRIER TO NEW LOCATION. 3. REMOVE WEST SIDE EXISTING GUARDRAIL.

© EXISTING BRIDGE

SHLDR.

6'-0"

WORK ZONE



AS NOTED CARDNO, INC. MAV MAV

380 PARK PLACE BLVD. SUITE 300 CLEARWATER, FLORIDA 33759 CERTIFICATE OF AUTHORIZATION 29915


PROJECT NO. 225338

DATE

4/2016

11/23/2016

REVISIONS



BRIDGE NO. 134026 AS NOTED CARDNO, INC. DATE SHEET 4/2016 380 PARK PLACE BLVD, SUITE 300 Manatee MANATEE COUNTY NO. TYPICAL SECTION CLEARWATER, FLORIDA 33759 **PUBLIC WORKS** PROJECT NO. RFN FL. LICENSE NO. 1 B2-4 CERTIFICATE OF AUTHORIZATION 29915 225338 REVISIONS 5:15:34 PM 11/23/2016 J:\00193\00193010.07\ms\struct\Br 134026\B02TypicalSection01.DGN




APPROXIMATE LOCATION OF STANDARD PENETRATION TEST BORING

B-1

	CORROSION TEST RESULTS												
Sample Location	RESISTIVITY ohm-cm	CHLORIDES ppm	SULFATES ppm	p <u>H</u>									
B-1 (33.5'-35') & B-2 (23.5'-25' & 28.5'-30')	3,100	21.6	<1.6	7.1									
			<u>Steel</u>	Concrete									
Substructure Environment Classification: Moderately Slightly Aggressive Aggressive													

BORING NO. B-1 B-2 STATION: 163+80 164+30 OFFSET: 35' Rt. 35' Rt. ELEVATION: +25' +/- +25' +/-



GENERAL LEGEND

- Asphaltic concrete over limestone gravel base
- Gray, dark gray, and brown fine SAND with trace to slight amounts of silt (SP, SP-SM)
- 2 Light gray silty, sandy CLAY (CL)
- Light gray to gray sandy, clayey SILT (ML) (Weathered Limestone)
- Gray to brown clayey SAND (SC)
- Gray to dark gray silty SAND with sand size to gravel size limestone gravel fragments (SM)
 - N Indicates the number of blows of a 140 pound hammer, freely falling a distance of 30 inches, required to drive a 2-inch diameter sampler 12 inches (ASTM D 1586)
- B-1 Standard Penetration Test (SPT) Boring and number
- SP Unified Soil Classification System Group Symbol (ASTM D 2487)
- +17.0 V Elevation of groundwater (feet-NGVD) & date measured
 - 50/3 Indicates fifty SPT hammer blows were required to drive the sampler 3 inches
 - MC Moisture Content (%)
 - -200 Amount Finer Than The U.S. Standard No. 200 Sieve (%)

NOTES

- (1) Borings were drilled on March 14, 2016 using a track-mounted BR-2500 drilling rig.
- (2) Strata boundaries are approximate and represent soil strata at each test hole location only. Soil transitions may be more gradual than implied.
- (3) Groundwater depths shown on the subsurface profiles represent the groundwater surfaces on the date shown. Groundwater level fluctuations should be anticipated throughout the year.
- (4) Station, offset, and elevation were estimated based on the topographic survey provided by Cardno.

ENGINEERING CLASSIFICATION (SAFTEY HAMMER)

GRANULAR MATERIALS SILTS AND CLAYS

Relative Density	SPT BLOW-COUNTS	Consistency	BLOW-COUNTS
Very Loose Loose Medium Dense Dense Very Dense	Less than 4 4 - 10 10 - 30 30 - 50 Greater than 50	Very Soft Soft Firm Stiff Very Stiff Hard	Less than 2 2 - 4 4 - 8 8 - 15 15 - 30 Greater than 30

STANDARD PENETRATION TEST DATA
SPOON INSIDE DIA. 1.375 inch
SPOON OUTSIDE DIA. 2.00 inches

SPOON OUTSIDE DIA.

AVG. HAMMER DROP
HAMMER WEIGHT

1.070 iniches
2.00 inches
30 inches
140 pounds

James M. Jackson, P.E. FL Reg. No. 77733

J D	S_NOTEI	SCALE				
8 1	JM J	DESIGNED BY				
	OIVIC	DRAWN BY				
۱۱۵	JM	DICAMIN BI	JMJ	5-11-16	ADD BORING ELEVATION	1
4		CHECKED BY	JMJ	11-28-16	ADD SIGNATURE BLOCK	2
,	KEA		ΒY	DATE	REVISIONS	No.

DUNKELBERGER ENGINEERING & TESTING

MJ 8260 VICO COURT, UNIT B

MJ SARASOTA, FLORIDA 34240


CERTIFICATE OF AUTHORIZATION 6870

DATE
4/2016

PROJECT NO.
225338



DESIGN ENGINEER	REPORT OF CORE BORINGS	SHEET
JAMES M. JACKSON	FOR STRUCTURES	NO.
FL. LICENSE NO. 77733	PROJECT NAME: RYE ROAD BRIDGE 134026 MANATEE COUNTY, FLORIDA	



						1	PILE DATA T	ABLE										
		1	NSTALLATION	CRITERIA					08000		DESIGN (DESIGN CRITERIA						
BENT NUMBER PILE NUMBER	PILE SIZE (in.)	NOMINAL BEARING RESISTANCE (tons)	NOMINAL UPLIFT RESISTANCE (tons)	MINIMUM TIP ELEVATION (ft.)	PILE	REQUIRED JET ELEVATION (ft.)	PREFORM	FACTORED DESIGN LOAD (tons)	FACTORED DESIGN UPLIFT LOAD (tons)	DOWN	TOTAL SCOUR RESISTANCE (tons)	NET SCOUR RESISTANCE (tons)	100-YEAR SCOUR ELEVATION (ft.)	LONG TERM SCOUR ELEVATION (ft.)	IPRES	O UPLI		
1-7	HP14x73	40	N/A	0.0	. N/A	N/A	N/A	24	N/A	N/A	2	0	12.8	12.8	0.65	0.65		
2-6	HP14x73	55	N/A	0.0	40	N/A	N/A	34	N/A	N/A	2	0	12.8	12.8	0.65	0.65		
3-7	HP14x73	40	N/A	0.0	N/A	N/A	N/A	24	N/A	N/A	2	0 .	12.8	12.8	0.65	0.65		

PILE CUT-OFF ELEVATIONS											
PIER or BENT NUMBER	PILE 6	PILE 7									
1	NA	22.8									
2	22.8	NA									
3	NA	22.8									

Factored Design Load + Net Scour Resistance + Down Drag ≤ Nominal Bearing Resistance

TENSION RESISTANCE

- The ultimate side friction capacity that must be obtained below the 100 year scour elevation to resist pullout of the pile (Specify only when design requires tension capacity).

TOTAL SCOUR RESISTANCE

- An estimate of the ultimate static side friction resistance provided by the scourable soil.

NET SCOUR RESISTANCE

- An estimate of the ultimate static side friction resistance provided by the soil from the required preformed or jetting elevation

to the scour elevation.

100-YEAR SCOUR ELEVATION - Estimated elevation of scour due to the 100 year storm event.

LONG TERM SCOUR ELEVATION - Estimated elevation of scour used in design for extreme event loading.

PILE INSTALLATION NOTES:

Piles to be coated per FDOT Standard Specification 560.

Contractor to verify location of all utilities prior to any pile installation activities.

Minimum Tip Elevation is required for lateral stability.

When a required jetting elevation is shown, the jet shall be lowered to the elevation and continue to operate at this elevation until the pile driving is completed. If jetting or preforming elevations differ from those shown on the table, the Engineer shall be responsible for determination of the required driving resistance.

No jetting will be allowed without the approval of the Engineer.

The Contractor should not anticipate being allowed to jet piles below the 100-year scour elevation or required jet elevation, whichever is deeper.

At each Bent, pile driving is to commence at the center of the Bent and proceed outward.

PILE CUT-OFF NOTE:

Contractor shall verify the existing top-of-bent elevations on which the pile cut-off elevations are based. Refer to the End Bent plan sheet for more information.

BRIDGE NO. 134026

AS NOTED CARDNO, INC. 380 PARK PLACE BLVD, SUITE 300 CLEARWATER, FLORIDA 33759 CERTIFICATE OF AUTHORIZATION 29915 REVISIONS

DATE 4/2016 PROJECT NO.

225338



Innates MANATEE COUNTY **PUBLIC WORKS**


NANDA B. KELLE FL. LICENSE NO 65632


PILE DATA TABLE


B2-7


SHEET


4:43:26 PM 11/23/2016 J.\00193\00193010.07\ms\struct\Br 134026\B02PileData01.dgm














2'-7"


1'-31/2"

1'-31/2"

5-8P01

4P03

HP14X73



SECTION A-A

SECTION B-B

SECTION C-C

NOTES:

1. WORK THIS SHEET WITH THE INTERMEDIATE BENT SHEET.

DESIGNED BY

SEALE AS NOTED CARDNO, INC.

DESIGNED BY ABK

JRAWN BY

AAM

CLEARWATER,

CERTIFICATE CO

CARDNO, INC. 380 PARK PLACE BLVD, SUITE 300 CLEARWATER, FLORIDA 33759 CERTIFICATE OF AUTHORIZATION 29915 PROJECT NO. 225338

Manatee MANATEE COUNTY
County PUBLIC WORKS

E A GENCHE A PAR A

BRIDGE NO. 134026


SHEET
NO.
NO.


DETAILS

B2-I3

3-26 PM

11/23/2016





14- 5 8- 6 3-10 14- 5 1- 6 LOC 14- 7 8-10 3-10 14- 7 1- 6	BARS 4710N 36 60 30 4 59 4710N 36 60 30	\$U 1 1 1 1 10 \$U \$U \$U \$U \$U \$U \$U \$U \$U \$	A G PERS	FT IN FR TRUCTURE 14- 4 1/4 8- 6 0-11 14- 4 1/4 1- 0 TRUCTURE 14- 6 1/2 8-10 0-11	O- 6 O- 6 DECK SPAN			NO. I		H FT IN FR RED = 1	FT IN FR	FT IN FR	N NO A	ANG
14-5 8-6 3-10 14-5 1-6 LOC 14-7 8-10 3-10 14-7 1-6 LOC 14-0 24-0 36-10 43-1 53-11	36 60 30 4 59 4710N 36 60 30 4 59	SU 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1	PERS	14- 4 1/4 8- 6 0-11 14- 4 1/4 1- 0 TRUCTURE 14- 6 1/2 8-10 0-11	O- 6 O- 6 DECK SPAN			N0. I			1 1 1 1 1			
14-5 8-6 3-10 14-5 1-6 LOC 14-7 8-10 3-10 14-7 1-6 LOC 14-7 1-6 14-7 1-6 14-7 1-6	36 60 30 4 59 4710N 36 60 30 4 59	1 1 1 10 SU 1 1 1 4 1 10	PERS	14- 4 1/4 8- 6 0-11 14- 4 1/4 1- 0 STRUCTURE 14- 6 1/2 8-10 0-11	0- 6 0- 6 DECK SPAN									
8-6 3-10 14-5 1-6 LOC. 14-7 8-10 3-10 14-7 1-6 LOC. 1 4-10 2 4-0 3 6-10 4 3-1 5 3-11	60 30 4 59 4710N 36 60 30 4 59	5U 1 1 1 1 1 1 1 10	# 4 4 PERS	8- 6 0-11 14- 4 1/4 1- 0 STRUCTURE 14- 6 1/2 8-10 0-11	0- 6 0- 6 DECK SPAN	2		NO 4						
3-10 14-5 1-6 LOC 14-7 8-10 3-10 14-7 1-6 LOC 1 4-10 2 4-0 3 6-10 4 3-1 5 3-11	30 4 59 4710N 36 60 30 4 59	\$U 10 \$U 1 1 1 4 10	# # # # # # # # # # # # # # # # # # #	0-11 14- 4 ½ 1- 0 STRUCTURE 14- 6 ½ 8-10 0-11	0- 6 DECK SPAN	2		Nn 4						
14-5 1-6 LOC 14-7 8-10 3-10 14-7 1-6 LOC 1 4-10 2 4-0 3 6-10 4 3-1 5 3-11	4 59 36 60 30 4 59 ATION 5	1 10 SU 1 1 1 4 1	PERS	14- 4 1/2 1- 0 TRUCTURE 14- 6 1/2 8-10 0-11	0- 6 DECK SPAN	2		NO 4						
1-6 LOC 14-7 8-10 3-10 14-7 1-6 LOC 1 4-10 2 4-0 3 6-10 4 3-1 5 3-11	36 60 30 4 59	10 SU 1 1 1 4 1	PERS	1- 0 TRUCTURE 14- 6 ½ 8-10 0-11	0- 6 DECK SPAN	2		NO 4						
14-7 8-10 3-10 14-7 1-6 LOC: 1 4-10 2 4-0 3 6-10 4 3-1 5 3-11	36 60 30 4 59	SU 1 1 4 1 10	PERS	14- 6 ½ 8-10 0-11	DECK SPAN	2		NO 1						$\exists !$
14-7 8-10 3-10 14-7 1-6 LOC 1 4-10 2 4-0 3 6-10 4 3-1 5 3-11	36 60 30 4 59 ATION	1 1 4 1 10	4 4	14- 6 ½ 8-10 0-11		2		NO A				1		
14-7 8-10 3-10 14-7 1-6 LOC 1 4-10 2 4-0 3 6-10 4 3-1 5 3-11	36 60 30 4 59 ATION	1 1 4 1 10	4 4	14- 6 ½ 8-10 0-11		2		NO I						
8-10 3-10 14-7 1-6 LOC: 1 4-10 2 4-0 3 6-10 4 3-1 5 3-11	60 30 4 59 ATION	1 4 1 10	4 4	8-10 0-11				/	REQUIR	RED = 1				
8-10 3-10 14-7 1-6 LOC: 1 4-10 2 4-0 3 6-10 4 3-1 5 3-11	60 30 4 59 ATION	1 4 1 10	4 4	8-10 0-11				₩					\rightarrow	
3-10 14-7 1-6 LOC 1 4-10 2 4-0 3 6-10 4 3-1 5 3-11	30 4 59 ATION	1 10	4 4	0-11				-					\rightarrow	
14-7 1-6 LOC 1 4-10 2 4-0 3 6-10 4 3-1 5 3-11	4 59 ATION 5	10			0.0			+					\rightarrow	 }
1-6 LOC 1 4-10 2 4-0 3 6-10 4 3-1 5 3-11	59 ATION 5	10	-	1 4 6 1/	0- 6			+				 	\rightarrow	
LOC. 1 4-10 2 4-0 3 6-10 4 3-1 5 3-11	ATION 5		 	14- 6 1/2				 						
1 4-10 2 4-0 3 6-10 4 3-1 5 3-11	5	EN	ı I -	1-0	0- 6			┼				 	\rightarrow	
1 4-10 2 4-0 3 6-10 4 3-1 5 3-11	5	_ <u> </u>	0 00	A17 1				NO I	250LIT	RED = 1	L		Щ	 ∤}
2 4-0 3 6-10 4 3-1 5 3-11				141 1				7VO. 7	120017	120 - 1			$\overline{}$	┵
2 4-0 3 6-10 4 3-1 5 3-11		1	$\vdash \vdash$	4-10	<u> </u>			+				 	+	 -∤ŀ
3 6-10 4 3-1 5 3-11	. 4			2-0	2- 0			+-				 	\dashv	60
4 3- 1 5 3-11	6		\vdash	6-10				1					\vdash	
5 3-11	$+\frac{5}{1}$	_	\vdash	1-2	1-11			\dagger					\vdash	60
	$+\frac{i}{i}$			1-11	2- 0			†				. 1	\neg	19
	1			0-10	1-11			\uparrow					\neg	63
7 6-9	5			2- 6	1- 5	1- 5	1- 5	\dagger		4			\sqcap	
8 5-4	1			2- 6	1- 5	1-5		1					\Box	\neg 11
9 5-0	30	11	\sqcap	2- 0	1- 6	1- 6		1						\neg 1
0 4-11	2	11		1-11	1-6	1-6								-11
1 6-6	2			2- 6	2- 0	2- 0								
2 3-10	4	10		2- 6	1 4									
3 6-2	6	1		6- 2				<u> </u>						
4 5-0	6	12		2- 6	2- 6									30
	\perp		ot											
LBC	ATION	1	NTER	MEDIATE B	ENT 2			NO. 1	REQUIF	RED = 1				
	 		\sqcup					1					\vdash	
								1					\rightarrow	
	+							 					\vdash	——
		+	1-1-		-			-				\vdash	\vdash	——
_	_					1- /		┼				\vdash		——
3-10	4	10	 -	2-0	1- 4			+				 	\rightarrow	
1.00	ATION	- FA	0 86	AIT 3				NO A	פרטונו	250 - 1				11
T 200.	11014	E14		1				1	120017	ED = 1			$\overline{}$	II
1 - 5- 2	5	1	\vdash	5- 2				+				 	_	-
	+				5- 6			1	-				_	60
	-			7- 0				1					-	
				1-2	1-11			\uparrow					\neg	60
					2- 0			Í					\neg	19
	+			0-10	1-11			1					$\neg \uparrow$	63
				2- 6	1-5	1- 5	1-5	1					\Box	$\neg \Box$
5- 4	-	+		2- 6	1- 5	1- 5			1					11
9 5- 0				2- 0	1- 6	1- 6								
				1-11	1- 6	1- 6								
				2- 6	2- 0	2- 0			- 1				\Box]
2 3-10	4	10	Ш	2- 6	1- 4]				\Box	
LOC	ATION	AP	PROA	CH SLAB E	ND BENT 1	10		NO. I	REQUIR	RED = 1	7			
	,		$\sqcup \sqcup$					1					\Box	
		_	-					-					\Box	
		+	+					+					$\vdash \vdash$.
1 5 0	1			5-9	L .		L						$oldsymbol{ol}}}}}}}}}}}}}}}}}}$	
J 5- 9														
<u> </u>														
	1 5-5 2 7-11 3 5-1 4 5-3 5 3-10 LOC 1 5-2 2 8-5 3 7-0 4 3-1 6 2-9 7 6-9 8 5-4 9 5-0 0 4-11 1 6-6 2 3-10 LOC LOC 7-8	1 5- 5 5 2 7-11 7 3 5- 1 1 4 5- 3 1 5 3-10 4 LOCATION 1 5- 2 5 2 8- 5 4 3 7- 0 6 4 3- 1 1 6 3-11 1 6 2- 9 1 7 6- 9 6 8 5- 4 1 9 5- 0 18 9 5- 0 18 1 6- 6 2 2 3-10 4 LOCATION	1 5- 5 5 1 2 7-11 7 4 3 5- 1 1 11 4 5- 3 1 11 5 3-10 4 10 LOCATION EN 1 5- 2 5 1 2 8- 5 4 12 3 7- 0 6 1 4 3- 1 1 12 6 2- 9 1 12 6 2- 9 1 12 6 2- 9 1 12 7 6- 9 6 37 8 5- 4 1 11 9 5- 0 18 11 1 6- 6 2 11 2 3-10 4 10 LOCATION AP LOCATION AP	1 5- 5 5 1 2 7-11 7 4 4 4 4 3 5- 3 1 11 1 5- 3 1 11 1 1 5- 3 1 11 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1	1 5-5 5 1 5-5 5 2 7-11 7 4 4 4 4 1-6 3 5-1 1 11 2-1 4 5-3 1 11 1 2-1 5 5 5 7 7 1 1 11 2-1 5 7 7 1 1 11 2-1 7 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1	1 5-5 5 1 5-5 2 2 7-11 7 4 4 4 1-6 2-1 3 5-1 1 11 2-1 1-6 4 5-3 1 11 2-1 1-7 5 3-10 4 10 2-6 1-4 LOCATION END BENT 3 1 5-2 5 1 5-2 2 2 8-5 4 12 2-11 5-6 3 7-0 6 1 7-0 4 4 3-1 1 12 1-2 1-11 2-0 6 4 3-1 1 12 1-11 2-0 6 5 3-11 1 12 1-11 2-0 6 6 2-9 1 12 0-10 1-11 6 6 2-9 1 11 12 1-11 1-5 8 8 5-4 1 11 2-6 1-5 8 8 5-4 1 11 2-6 1-5 9 9 5-0 18 11 2-0 1-6 1-5 9 9 5-0 18 11 1-11 1-6 1-6 0 1 4-11 4 11 1-11 1-6 1-6 0 2 3-10 4 10 2-6 1-4 LOCATION APPROACH SLAB END BENT 1 LOCATION APPROACH SLAB END BENT 1	1 5-5 5 1 5-5 5 1 5-5 2 1 1 6 1-6 1-6 1-6 1-6 1-6 1-7 1-7 1-7 1-7 1-7 1-7 1-7 1-7 1-7 1-7	1 5-5 5 1 5 1 5-5 5 2 1 5-6 3 5 1 1 1 1 1 2-1 1 1-6 1-6 4 5-3 1 1 1 1 1 2-1 1 1-7 1-7 1-7 5 3-10 4 10 2-6 1-4 5-3 1 1 1 1 2 2-11 5-6 3 7-0 6 1 7-0 4 3-1 1 1 1 1 2 1-1 1 2-0 6 2-9 1 1 1 1 1 2-6 1-5 1-5 1-5 8 5-4 1 1 11 2-6 1-6 1-6 1-6 1-6 1-6 1-6 1-6 1-6 1-6 1	1 5-5 5 1 5 1 5-5 2 1 1 6 1-6 4 1 7 1 7 4 4 4 4 1-6 2-1 1 1 7 1 7 4 4 4 4 1 7 6 2-1 1 1 7 1 7 1 7 1 7 1 7 1 7 1 7 1 7 1 7	1 5-5 5 5 1 5-5 7 2 7-11 7 4 4 4 1-6 2-1 7 3 5-1 1 11 2-1 1-6 1-6 4 4 5-3 1 11 2-1 1-7 1-7 5 5 3-10 4 10 2-6 1-4 7 LOCATION END BENT 3 NO. REOUIF 1 5-2 5 1 5-2 7 2 8-5 4 12 2-11 5-6 7 3 7-0 6 1 7-0 7 4 3-1 1 12 1-2 1-11 7 6 3-11 1 12 1-11 2-0 7 6 2-9 1 12 0-10 1-11 7 7 6-9 6 37 2-6 1-5 1-5 7 8 5-4 1 11 2-6 1-6 1-6 7 9 5-0 18 11 2-0 1-6 1-6 7 1 6-6 2 11 2-6 2-0 2-0 7 2 3-10 4 10 2-6 1-4 7 LOCATION APPROACH SLAB END BENT 1 NO. REOUIF	1 5-5 5 1 5 1 5-5 5 2 7-11 7 4 4 4 4 1-6 2-1 7 1-7 1-7 1-7 1-7 1-7 1-7 1-7 1-7 1-7	1 5-5 5 1 1 5-5 6 2-1 3 5-1 1 11 2-1 1-6 1-6 4 5-3 1 11 1 2-1 1-7 1-7 1-7 5 3-10 4 10 2-6 1-4 1 1 1 1 2 1-2 1 1-1 1 1 1 1 1 1 1 1 1 1	1 5-5 5 1 5-5 7-11 7 4 4 4 1-6 2-1 7-11 7 4 4 4 1-6 2-1 7-11 7 4 4 4 1-6 2-1 7-11 7 7 1-7 1 1-7	1 5-5 5 1 5-5 5 1 5-5 5 1 5-5 5 1 11 2-1 1-6

MA	RK	LENGTH	NO	TYP	STY	B		ζ .	D	<i>E</i>	F	H	3	K	N	0
SIZE	DE5	FT IN	BAR5	BAR	A	FT IN	FR	FT IN FR	FT IN FR	FT IN FR	FT IN FR	FT IN FR	FT IN FR	FT IN FR	NO	ANG
8	A4	5- 9	1	1		5- 9										
5	A5	3- 0	1	_1		2-11										
8	A6	3- 0	1	1		2-11										
5	A7	8- 0	1	1		7-11										
. 8	A8	8- 0	1	1		7-11										
5	A9	VARY	22			6-8										
		7- 9	0	- 1	Ш	8-8	1/4									
5	A10	3- 5	22	1		3- 5										
6	AII	1- 6	5	1		1- 6										
		LOCA	TION	AP	PRO.	ACH SLAE	E	ND BENT 3			NO. REQUI	RED = 1				
5	ΑI	7- 8	8			7- 8		·						,		
8	A2	7- 8	10	1		7- 8										
5	A3	5-10	1	- 1		5- 9										
8	A4	5-10	1	1		5- 9										
5	A5	3- 1	1	1		3- 0										
8	A6	3- 1	1	1		3- 0	1/2									
5	A7	8- 0	1	1		7-11										
8	A8	8- 0	1	- 1		7-11										
5	A9	VARY	22	1		6-11										
		8- 0	0	1		9- 0	1/4									
5	AIO	3- 5	22	I		3- 5										
6	All	1- 6	5			1- 6										

END OF LIST

BRIDGE NO. 134026

AS NOTED CARDNO, INC. DATE 4/2016 380 PARK PLACE BLVD, SUITE 300 CLEARWATER, FLORIDA 33759 PROJECT NO. CERTIFICATE OF AUTHORIZATION 29915 225338 REVISIONS DATE BY

Manatee MANATEE COUNTY
County PUBLIC WORKS

65632

REBAR LIST

NO. B2-I6

SHEET

11/23/2016

J:\00193\00193010.07\ms\struct\8r 134026\802RebarList01.dgn

MANATEE COUNTY PUBLIC WORKS DEPARTMENT

CONTRACT PLANS

MANATEE COUNTY (6086160)

RYE ROAD FROM SR 64 TO UPPER MANATEE RIVER ROAD

INDEX OF PEDESTRIAN BRIDGE PLANS

SHEET NO.

P-2

P-3

P-4 P-5

P-6

P-7

P-8

SHEET DESCIPTION

PEDESTRIAN BRIDGE LOCATION 1

PEDESTRIAN BRIDGE LOCATION 2

END BENT DETAILS (1 OF 2)


END BENT DETAILS (2 OF 2)

REPORT OF CORE BORINGS (1) REPORT OF CORE BORINGS (2)

KEY SHEET

GENERAL NOTES


PEDESTRIAN BRIDGES



PEDESTRIAN BRIDGE SHOP DRAWINGS TO BE SUBMITTED TO: CHESTER A. SMITH III, P.E. HDR ENGINEERING, INC. 2601 CATTLEMEN ROAD, SUITE 400 SARASOTA, FLORIDA 34232


PLANS PREPARED BY:
HDR ENGINEERING, INC.
2601 CATTLEMEN ROAD, SUITE 400
SARASOTA, FLORIDA 34232
(941) 342-2700
WWW.HDRINC.COM
FBPR CERTIFICATE OF AUTHORIZATION NO. 4213
VENDOR NO. 47-0680568
CONTRACT NO. C9480

NOTE: THE SCALE OF THESE PLANS MAY HAVE CHANGED DUE TO REPRODUCTION.



PEDESTRIAN BRIDGE PLANS ENGINEER OF RECORD: CHESTER A. SMITH III

P.E. NO.: 70756



FISCAL YEAR	SHEET NO.
17	P-1

GENERAL NOTES

DESIGN SPECIFICATIONS:

AMERICAN ASSOCIATION OF STATE HIGHWAY AND TRANSPORTATION OFFICIALS (AASHTO), LRFD BRIDGE DESIGN SPECIFICATIONS, 7th EDITION WITH 2016 INTERIMS. AASHTO LRFD, GUIDE SPECIFICATIONS FOR DESIGN OF PEDESTRIAN BRIDGES, 2ND EDITION

WITH 2015 INTERIMS

THE ALUMINUM ASSOCIATION, SPECIFICATIONS AND GUIDELINES FOR ALUMINUM STRUCTURES, LATEST EDITION

DESIGN METHODOLOGY:

LOAD AND RESISTANCE FACTOR DESIGN METHOD (LRFD) USING STRENGTH, SERVICE AND FATIGUE

DESIGN LOADING:

LIVE LOAD

= H5 LOADING DESIGN TRUCK

PEDESTRIAN LOADING (PEDESTRIAN BRIDGE) = 90 PSF

DEAD LOADS:

REINFORCED CONCRETE UNIT WEIGHT = 150 PCF

FOUNDATION:

THE FOUNDATION FOR THE CONCRETE SPREAD FOOTING SHALL BE CONSTRUCTED IN ACCORDANCE WITH SECTION 455 OF THE SPECIFICATIONS.

SOIL BELOW FOOTING IS TO HAVE A MINIMUM ALLOWABLE BEARING CAPACITY OF 2.025 KIPS/SQ. FT. FOR LEVEL GROUND. THE BOTTOM OF THE FOOTING SHALL BE A MINIMUM OF 33 INCHES BELOW ADJACENT COMPACTED GRADE ON ALL SIDES.

THE FOUNDATIONS HAVE BEEN DESIGNED USING THE FOLLOWING ESTIMATED TOTAL LOADS FROM THE PEDESTRIAN BRIDGE WITH APPLICABLE STRENGTH AND SERVICE LIMITS APPLIED.

UNFACTORED LOADS PER BRIDGE ($\Upsilon = 1.0$) DEAD = 4.833 LBSLIVE = 36,000 LBS (PEDESTRIAN LOADING) HORIZONTAL WIND = 19,471 LBS OVERTURNING WIND = 9,333 LBS

IF THE CONTRACTOR PROVIDES A PEDESTRIAN BRIDGE THAT EXCEEDS THESE LOADS, THEN THE CONTRACTOR MUST SUBMIT CALCULATIONS SIGNED AND SEALED BY A PROFESSIONAL ENGINEER LICENSED IN THE STATE OF FLORIDA TO THE COUNTY FOR REVIEW AND APPROVAL SHOWING THAT THE SPREAD FOOTING DIMENSIONS, REINFORCING STEEL SIZE, AND SPACING ARE ADEQUATE.

VERTICAL DATUM:

ALL ELEVATIONS REFER TO THE NATIONAL GEODETIC VERTICAL DATUM (NGVD) OF 1929.

DIMENSIONS:

ALL DIMENSIONS IN THE PLANS ARE MEASURED IN FEET AND INCHES.

CONCRETE:

ALL CONCRETE FOUNDATIONS SHALL BE FDOT CLASS IV AND HAVE A MINIMUM 28 DAY COMPRESSIVE STRENGTH, f'c = 5500 PSI

CONCRETE COVER:

CONCRETE COVER IS 4" UNLESS NOTED OTHERWISE IN THE PLAN SET AND DO NOT INCLUDE PLACEMENT AND FABRICATION TOLERANCES. SEE SECTION 415 OF THE SPECIFICATIONS FOR ALLOWABLE TOLERANCES.

JOINTS IN CONCRETE:

CONSTRUCTION JOINTS WILL BE PERMITTED ONLY AT THE LOCATIONS INDICATED IN THE PLANS. ADDITIONAL CONSTRUCTION JOINTS OR ALTERATIONS TO THOSE SHOWN SHALL REQUIRE APPROVAL OF THE ENGINEER.

CHAMFERS:

PROVIDE 34" CHAMFER ON ALL EXPOSED SURFACES.

REINFORCING STEEL:

MATERIAL:

REINFORCING STEEL SHALL BE ASTM A615, GRADE 60.

REVISIONS

PLACEMENT:

ALL DIMENSIONS PERTAINING TO THE LOCATION OF REINFORCING ARE TO THE CENTERLINE OF BAR, EXCEPT WHERE THE CLEAR DIMENSION IS SHOWN TO THE FACE OF CONCRETE.

AS NOTED HDR ENGINEERING, INC.

DAR

AT

2601 CATTLEMEN ROAD, SUITE 400

CERTIFICATE OF AUTHORIZATION 4213

SARASOTA, FLORIDA 34232

ENVIRONMENT:

SUBSTRUCTURE - CONCRETE: MODERATELY AGGRESIVE (PH = 5.7, RESISTIVITY = 1,800 OHM-CM)

ARREVIATIONS. F = EXPANSION BEARINGFFBW = FRONT FACE OF BACKWALL E.F. = EACH FACE

PEDESTRIAN BRIDGE:

MATERIALS:

PRIMARY STRUCTURAL MEMBERS SHALL BE 6061-T6 ALUMINUM SECONDARY STRUCTURAL MEMBERS SHALL BE 6000 SERIES ALUMINUM BRIDGE DECKING SHALL BE ALUMINUM ALLOY 6061-T6 EXTRUDED

DEFLECTIONS REQUIREMENTS: VERTICAL = SPAN / 400HORIZONTAL = SPAN / 500

THE FUNDAMENTAL FREQUENCY OF THE UNLOADED PEDESTRIAN BRIDGE SHALL BE NO LESS THAN 3.0 HERTZ TO AVOID THE FIRST HARMONIC.

BRIDGE SHALL BE CAMBERED TO OFFSET THE DEAD LOAD.

DEPTH OF BRIDGE STRUCTURE FROM TOP OF DECK TO BOTTOM OF LOWEST CHORD IS ASSUMED TO BE 1'-51/2" MAXIMUM. BRIDGE SUPPLIER TO PROVIDE 1'-51/2" MAX DEPTH FROM TOP OF DECK TO BOTTOM OF LOWEST CHORD.

ANCHOR BOLTS:

THE CONTRACTOR IS RESPONSIBLE FOR PROVIDING ANCHOR BOLTS THAT MEET PREFABRICATED BRIDGE SUPPLIER REQUIREMENTS.

COVER PLATES:

PROVIDE ADA COMPLIANT COVER PLATE SYSTEM AT BEGIN AND END BRIDGE LOCATIONS WHERE PEDESTRIANS TRANSITION BETWEEN SURFACES. THE COVER PLATE SHALL BE RUBBER ENCAPSULATED STEEL COVER SYSTEM TO AVOID CORROSION BETWEEN DISSIMILAR MATERIALS.

UTILITIES:

LOCATION AND TYPE OF UTILITIES SHOWN IN THE BRIDGE PLANS ARE APPROXIMATE. FOR UTILITY DISPOSITIONS AND ADDITIONAL INFORMATION, REFER TO THE UTILITY ADJUSTMENTS PLANS.


BID ITEM NOTES:

PAYMENT FOR INCIDENTAL ITEMS NOT SPECIFICALLY COVERED IN THE INDIVIDUAL PAY ITEMS SHALL BE INCLUDED IN THE CONTRACT UNIT PRICE FOR THE PAY ITEMS.

NO SEPARATE PAYMENT WILL BE MADE FOR EXCAVATIONS FOR CONSTRUCTION OF FOOTINGS. ALL COSTS FOR EXCAVATION SHALL BE INCIDENTIAL TO THE ELEMENT REQUIRING SUCH WORK.

THE COST OF THE COVER PLATES (4 TOTAL) SHALL BE INCLUDED WITH THE COST OF THE CLASS IV (SUBSTRUCTURE) CONCRETE, PAY ITEM 400-4-5.

ESTIMATED QUANTITIES								
			QUANTITY					
ITEM	DESCRIPTION		LOC. 1	LOC. 2	TOTAL			
400-4-5	CLASS IV (SUBSTRUCTURE)	C.Y.	15.82	15.82	31.64			
415-1-5	REINFORCING STEEL (SUBSTRUCTURE)	LBS.	1506	1506	3012			
530-3-4	RIPRAP-RUBBLE, DITCH LINING	TN.	20.76	22.62	43.38			
PB 1	PEDESTRIAN BRIDGE	EA.	1	1	2			



TYPICAL SECTION

DESIGN ENGINEER CHESTER A. SMITH III FL. LICENSE NO. 70756

GENERAL NOTES

SHEET NO P-2


DATE 11/2017


PROJECT NO.


225338

County

Manatee MANATEE COUNTY PUBLIC WORKS









NOTES:

- PROVIDE COVER PLATE AT BEGIN / END BRIDGE FOR TRANSITION FROM BRIDGE SURFACE TO CONCRETE
- 2. THE FFBW IS LOCATED 2 1/2 INCHES BEYOND THE PEDESTRIAN BRIDGE END POST TO PROVIDE CLEARANCE FOR THE BASE PLATE.
- 3. FOR GRADING DETAILS, SEE END BENT DETAILS (2 OF 2).
- DENOTES BORING LOCATIONS. FOR BORING DATA, SEE REPORT CORE OF BORINGS SHEETS.

1							
					SCALE	NOTED	Н
		*				NOTED	
					DESIGNED BY	JA	26
					DD AWAY DV		
					DRAWN BY	DAR	Si
					CHECKED BY		C
	No.	REVISIONS	DATE	BY		AT	101

HDR ENGINEERING, INC. 2601 CATTLEMEN ROAD, SUITE 400 SARASOTA, FLORIDA 34232 CERTIFICATE OF AUTHORIZATION 4213

11/2017 PROJECT NO.

225338

Manatee MANATEE COUNTY **PUBLIC WORKS**


DESIGN ENGINEER CHESTER A. SMITH III


FL. LICENSE NO.


PEDESTRIAN BRIDGE LOCATION 2

SHEET NO.

P-4








(HANDRAIL NOT SHOWN FOR CLARITY)

GRADING DETAILS - PLAN



	DK	LENGTH	NO	TYP	CTV	В	C	D	Е	F	Н	J	K	N	Ø
IVIZ	RK	LENGIN	NO	III	311	<i>D</i>	-			57 JAV 50	ET IN ED	ET IN ED	ET IN ED	NO	ANG
SIZE	DES	FT IN	BARS	BAR	$A \mid G$	FT IN FR	FT IN FR	FT IN FR	FI IN FR	FI IN FR	FI IN FR	FIINTA	I I III I I	NO	ANO
	END BENT 1 OR 2 (NO. REQUIRED = 4)														
				1		-									
5	A1	6- 4	26	1		6- 4									
5	A2	11-10	16	1		11-10									
5	A3	3- 3	24	10		2- 5	0-10								
5	A4	4- 0	12	1		4- 0									
									44						
5	B1	11-10	11	1		11-10								-	-
5	B2	3-10	12	11		2- 2	0-10	0-10						-	-
4	<i>B3</i>	4- 1	12	11		0- 4	1-10 1/2	1-10 1/2						-	
														-	
5	C1	4- 4	8	1		4- 4								-	
														1	
		-	•												

l						
				SCALE	NOTED	H
				DESIGNED BY	NOTED	1
				DESIGNED BY	JA	2
				DRAWN BY		٦
				1	DAR	5
100				CHECKED BY	4.7	c
No.	REVISIONS	DATE	BY		AI	Ľ

HDR ENGINEERING, INC.

2601 CATTLEMEN ROAD, SUITE 400

SARASOTA, FLORIDA 34232

CERTIFICATE OF AUTHORIZATION 4213

11/2017 Manatee

PROJECT NO.
225338

DATE

Manatee MANATEE COUNTY
County PUBLIC WORKS

DESIGN ENGINEER
CHESTER A.
SMITH III
FL. LICENSE NO.

70756


END BENT DETAILS
(2 OF 2)

SHEET NO.

P-6

PM 3/13/20

PW:\007982\C0N0086775\000000000225338\13.00_CAD\12345615201\struct\B1EndBent02.DGN



NOTE:

THE LOCATIONS OF THE BORINGS WERE RECORDED IN THE FIELD BY TIERRA, INC. USING GARMIN ETREX
HAND-HELD GPS EQUIPMENT WITH A REPORTED
ACCURACY OF 10 FEET. THE GPS COORDINATES
RECORDED BY TIERRA WERE UTILIZED IN CONJUNCTION WITH MICROSTATION DESIGN FILES TO OBTAIN STATION, OFFSET, AND ELEVATION. THEREFORE, THE LOCATIONS OF THE BORINGS SHOULD BE CONSIDERED APPROXIMATE.

ENVIRONMENTAL CLASSIFICATION:

25

20

15

-5

-10

SUBSTRUCTURE CONCRETE: MODERATELY AGGRESSIVE (pH=5.7, RESISTIVITY=1,800 OHM-CM)

SUBSTRUCTURE STEEL: EXTREMELY AGGRESSIVE (pH=5.7)

TEST RESULTS: RESISTIVITY CHLORIDES SULFATES

1,800 TO 14,000 OHM-CM 30 TO 105 PPM <4.8 TO 204.1 PPM 5.7 TO 7.8

LEGEND

GRAY TO BROWN SAND TO SAND WITH SILT



LIGHT BROWN TO DARK BROWN SILTY SAND (SM)




BROWN TO DARK BROWN CLAYEY SAND (SC)



BROWN TO GREEN SANDY CLAY TO CLAY TO SILT



UNIFIED SOIL CLASSIFICATION SYSTEM (ASTM D 2487) GROUP SYMBOL AS DETERMINED BY VISUAL REVIEW AND LABORATORY TESTING ON SELECTED SAMPLES FOR CONFIRMATION OF VISUAL REVIEW.



HAND AUGERED TO VERIFY UTILITY CLEARANCE

PERCENT PASSING #200 SIEVE NATURAL MOISTURE CONTENT (%) NMC PIPLASTICITY INDEX (%)

NAVD NORTH AMERICAN VERTICAL DATUM OF 1988




APPROXIMATE SPT BORING LOCATION

GROUNDWATER LEVEL ENCOUNTERED DURING ∇ FIELD EXPLORATIONS

GROUNDWATER NOT APPARENT DUE TO THE INTRODUCTION OF DRILLING FLUID.

& SURVEY



	SAFETY HAMMER	AUTOMATIC HAMMER
GRANULAR MATERIALS-	SPT N-VALUE	SPT N-VALUE
RELATIVE DENSITY	(BLOWS/FT.)	(BLOWS/FT.)
VERY LOOSE LOOSE MEDIUM DENSE DENSE VERY DENSE SILTS AND CLAYS CONSISTENCY	LESS THAN 4 4 to 10 10 to 30 30 to 50 GREATER THAN 50 SPT N-VALUE (BLOWS/FT.)	LESS THAN 3 3 to 8 8 to 24 24 to 40 GREATER THAN 40 SPT N-VALUE (BLOWS/FT.)
VERY SOFT	LESS THAN 2	LESS THAN 1
SOFT	2 to 4	1 to 3
FIRM	4 to 8	3 to 6
STIFF	8 to 15	6 to 12
VERY STIFF	15 to 30	12 to 24
HARD	GREATER THAN 30	GREATER THAN 24

PEDESTRIAN BRIDGE

AS NOTED REVISIONS DATE

BOR # STA.

REF.

ELEV.

DATE

25

20

15

 \sim

ELEVATION

0

-5

-10

DRILLER

6

9

PED-1

108+24

B SURVEY

24.3 2/27/2017

J. SHAW

D-25

(SP/SP-SM)

SILTY SAND (SM)

(CL/CH/ML)

BORING TERMINATED AT

LATITUDE: N 27.48358 LONGITUDE: W 82.40346

ELEVATION -5.7 FT (NAVD)

HAMMER AUTOMATIC

TIERRA, INC. 7351 TEMPLE TERRACE HIGHWAY TAMPA, FLORIDA 33637 CERTIFICATE OF AUTHORIZATION 6486

BORING TERMINATED AT

LATITUDE: N 27.48364 LONGITUDE: W 82.40337

ELEVATION -5.7 FT (NAVD)

PED-2

109+16

B SURVEY 44' LT.

24.3

2/27/2017

J. SHAW

D-25

GRAY TO BROWN SAND TO SAND WITH SILT

GRAY TO BROWN SAND TO SAND WITH SILT (SP/SP-SM)

LIGHT BROWN TO DARK BROWN SILTY SAND (SM)

LIGHT BROWN TO DARK BROWN SILTY SAND (SM)

- BROWN TO GREEN SANDY CLAY TO CLAY TO SILT (CL/CH/ML)

DATE

3/2017

PROJECT NO.

225338

GNA

HAMMER AUTOMATIC

STA.

REF.

ELEV.

DATE

RIG

-200=3

-200=13

GRAY TO BROWN SAND TO SAND WITH SILT

BROWN TO GREEN SANDY CLAY TO CLAY TO SILT

LIGHT BROWN TO DARK BROWN

DRILLER

10

13

Manatee MANATEE COUNTY **PUBLIC WORKS**

DESIGN ENGINEER DANIEL R. RUEL FL. LICENSE NO.

82404

REPORT OF CORE BORINGS (1)

NO. P-7

SHEET